

DH-P3B-PV

DAHUA DH-P3B-PV 3,6mm 3MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera – 3MP sabit fokuslu (3.6mm) lensli, Wi-Fi dəstəklənən, Pan & Tilt imkanlı xarici IP kameradır. Gecəgörmə, ağıllı hərəkət aşkarlama və mobil tətbiq vasitəsilə uzaqdan idarəetmə ilə təhlükəsizliyi yüksək səviyyədə təmin edir.



Specifications

Model	DH-P3B-PV
Brand	Dahua
Meqapixel	3 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	30m
Micro SD	256Gb
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	1/2.7" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100,000 s
Illumination Distance	Up to 30 m (98.43 ft) (IR); Up to 30 m (98.43 ft) (Warm Light)
Illuminator On/Off Control	Auto
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	Pan: 0°–355°; Tilt: 0°–90°

Lens

Max. Aperture	F1.6
Field of View	H: 87°; V: 44°; D: 105°

Intelligence

Vehicle Detection	Yes
Human Detection	Yes

Video

Video Compression	H.265
Video Frame Rate	Main stream: 2304 × 1296@(1-25/30 fps) sub stream: 640 × 360@(1-25/30 fps) *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Resolution	3M (2304 × 1296); nHD (640 × 360)
------------	-----------------------------------

Video Bit Rate	H.265: 80 kbps–4096 kbps
----------------	--------------------------

Day/Night	Auto(ICR)/Color/B/W
-----------	---------------------

WDR	DWDR
-----	------

Motion Detection	Yes
------------------	-----

Smart Illumination	Yes
--------------------	-----

Image Rotation	0°/180°
----------------	---------

Audio

Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a

Network

Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n/ax 2.412-2.472 GHz, 2.4 G
Storage	Micro SD card (up to 256 GB)

Management Software	DMSS
---------------------	------

Mobile Client	iOS;Android
---------------	-------------

Certification

Certifications	CE
----------------	----

Power

Power Supply	12 VDC
Power Consumption	Basic: 1.56 W; Max.: 4.56 W (H.265+warm light on)
Environment	
Operating Temperature	-20 °C to +50 °C (-4 °F to +122 °F)
Operating Humidity	≤95%
Structure	
Casing Material	Plastic
Product Dimensions	116 mm × 138 mm × 139 mm (4.57" × 5.43" × 5.47") (L × W × H)
Net Weight	425 g (0.94 lb)