DAHUA

DH-P3D-3F-PV

Kod: 00-00005432 · Wifi kamera



DAHUA DH-P3D-3F-PV 2.8mm 3+3MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera – 3MP əsas və 3MP panoram linza ilə təchiz edilmiş, Wi-Fi dəstəkləyən, Pan & Tilt funksiyalı açıq hava IP kamerasıdır. Geniş görüntü sahəsi, hərəkət aşkarlama, gecəgörmə və ağıllı izləmə funksiyaları ilə mükəmməl müşahidə təmin edir.

Texniki göstəricilər

3 MP Meqapixel	**Wifi** Qoşulma
İkitərəfli səs Səs	**20m** Gecə görmə məsafəsi
256Gb Micro SD	**Outdoor** İş mühiti

Ətraflı məlumat

Camera	
Fixed Lens	
Image Sensor	1/2.8" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Illumination Distance	Up to 30 m (98.43 ft) (IR) Up to 20 m (65.62 ft) (Warm light)
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	-10° to 15°
Lens Type	Fixed-focal
Focal Length	2.8 mm
Max. Aperture	F1.6
Field of View	H: 95°; V: 53°; D: 110°
PT Lens	
Image Sensor	1/2.8" CMOS
Max. Resolution	2304 (H) × 1296 (V)
Illumination Distance	Up to 50 m (164.04 ft) (IR) Up to 40 m (131.23 ft) (Warm light)
Illuminator Number	2 (IR LED); 2 (Warm light)
Angle Adjustment	Pan: 0° to 352°; Tilt: 0° to 90°
Lens Type	Fixed-focal
Focal Length	6 mm
Max. Aperture	F1.6

Field of View	H: 53°; V: 29°; D: 62°
Intelligence	
Human Detection	Yes
Vehicle Detection	Yes
Audio and Video	
Video Compression	H.265
Video Frame Rate	Main stream: 2304 × 1296@15 fps sub stream: 640 × 360@15 fps *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.
Video Bit Rate	H.265: 512 kbps–4096 kbps
Day/Night	Auto(ICR)/Color/B/W
WDR	DWDR
Motion Detection	Yes
Image Rotation	0°/180°
Built-in MIC	Yes, built-in Mic
Built-in Speaker	Yes, built-in speaker
Audio Compression	G.711a
Network	
Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n/ax 2.412-2.472 GHz,2.4G,≤20dBm@2400-2483.5MHz
Wi-Fi Pairing	Bluetooth pairing
Storage	Micro SD card (support max. 256 GB)
Management Software	DMSS

Mobile Client	iOS;Android
General	
Certifications	CE
Power Supply	12 VDC
Power Consumption	Basic: 2.3 W Max.: 10 W (pulling stream+ IR + siren and light active deterrence)
Operating Temperature	–20 °C to +50 °C (–4 °F to +122 °F)
Operating Humidity	≤95% (RH), non-condensing
Protection	IP66
Casing Material	Plastic
Product Dimensions	159.4 mm × 119.1 mm × 210 mm (6.28" × 4.69" × 8.27") (L × W × H)
Net Weight	585 g (1.29 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az