

## DH-P5AS-PV

DAHUA DH-P5AS-PV 5MP Outdoor Fixed-focal Wi-Fi PT Network Camera – 5MP çözünlük, sabit fokuslu obyektiv, Wi-Fi bağlantısı və Pan & Tilt funksiyası ilə yüksək təhlükəsizlik təmin edir. Gecəgörmə, ağıllı hərəkət aşkarlama və mobil idarəetmə ilə ev və obyektlər üçün ideal xarici müşahidə kamerasıdır.



### Specifications

Model	DH-P5AS-PV
Brand	Dahua
Meqapixel	5 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	30m
Micro SD	256Gb
?? mühiti	Outdoor

## KEY FEATURES

## Camera

Image Sensor 1/2.7" CMOS

Max. Resolution 2880 (H) × 1620 (V)

## Min. Illumination

0.007 lux@F1.6 (Color, 30 IRE)

0.0007 lux@F1.6 (B/W, 30 IRE)

0 lux (Illuminator on)

Illumination Up to 30 m (98.43 ft) (IR)

Distance Up to 30 m (98.43 ft) (Warm light)

Illuminator Number 2 (Multi-core (IR + warm) light)

Angle Adjustment Pan: 0° to 345°

Tilt: 0° to 90°

Rotation: 0° to 345°

Lens Type Fixed-focal

Focal Length 4.0 mm

Max. Aperture F1.6

Field of View H: 78°; V: 42°; D: 92°

## Intelligence

Human Detection Yes

Vehicle Detection Yes

## Audio and Video

Video Compression H.265; H.264; H.264H; H.264B; MJPEG (Only supported by sub stream)

Video Frame Rate Main stream: 2880 × 1620@(1–25/30 fps)

sub stream: 640 × 360@(1–25/30 fps)

\*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate H.264: 32 kbps–6144 kbps;

H.265: 32 kbps–6144 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Motion Detection OFF/ON (4 areas, rectangular)

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker Yes, built-in speaker

Audio Compression G.711a; G.711Mu; PCM

## Network

Network Port RJ-45 (10/100 Base-T)

## Wi-Fi

IEEE 802.11a/b/g/n/ac/ax 2.4 G &amp; 5 G, EIRP≤20 dBm@2400–2483.5 MHz (CE), EIRP≤23 dBm@5150–5250 MHz (CE),

EIRP≤20 dBm@5250–5350 MHz (CE), EIRP≤20 dBm@5470–5725 MHz (CE), EIRP≤14 dBm@5725–5875 MHz (CE)

Wi-Fi Pairing Bluetooth pairing

Interoperability ONVIF (Profile S &amp; Profile G &amp; Profile T); CGI

---

<b>Storage</b>	Micro SD card (support max. 256 GB)
<b>Management</b>	Smart PSS Lite; DSS; DMSS
<b>Software</b>	
<b>Mobile Client</b>	Android;iOS
<b>Function</b>	
<b>Abnormal Sound Alarm</b>	Yes
<b>General</b>	
<b>Certifications</b>	CE
<b>Power Supply</b>	12 VDC (±30%)
<b>Power Consumption</b>	Basic: 2 W (12 VDC) Max.: 14 W (12 VDC) (illuminator intensity + red and blue active deterrence + speaker on + PT rotation + Wi-Fi pulling stream + WDR)
<b>Operating Temperature</b>	-30 °C to +55 °C (-22 °F to +122 °F)
<b>Operating Humidity</b>	≤95% (RH), non-condensing
<b>Protection</b>	IP66
<b>Camera Button</b>	Reset button
<b>Casing Material</b>	Plastic
<b>Product Dimensions</b>	125.4 mm × 110 mm × 140.3 mm (4.94" × 4.37" × 5.52") (L × W × H)
<b>Net Weight</b>	0.4 kg (0.88 lb)