

DH-P5D-5F-PV

DAHUA DH-P5D-5F-PV 2.8mm 5+5MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera, 5+5MP dual-lens quruluşu ilə yüksək keyfiyyətli görüntülər təqdim edir. 2.8mm obyektiv, Wi-Fi bağlantısı və Pan & Tilt funksiyası ilə geniş ərazini izləmə imkanı yaradır. Açıq məkan istifadəsi üçün ideal təhlükəsizlik həllidir.



Specifications

Model	DH-P5D-5F-PV
Brand	Dahua
Meqapixel	5 MP
Qo?ulma	Wifi
S?s	İkitərəfli səs
Gec? görm? m?saf?si	20m
Micro SD	256Gb
?? mühiti	Outdoor

KEY FEATURES

Camera

Fixed Lens

Image Sensor 1/3" CMOS

Max. Resolution 2880 (H) × 1620 (V)

Illumination Distance
Up to 30 m (98.43 ft) (IR)

Up to 20 m (65.62 ft) (Warm light)

Illuminator Number 2 (IR LED); 2 (Warm light)

Angle Adjustment -10° to 15°

Lens Type Fixed-focal

Focal Length 2.8 mm

Max. Aperture F1.6

Field of View H: 95°; V: 53°; D: 110°

PT Lens

Image Sensor 1/3" CMOS

Max. Resolution 2880 (H) × 1620 (V)

Illumination Distance
Up to 50 m (164.04 ft) (IR)

Up to 40 m (131.23 ft) (Warm light)

Illuminator Number 2 (IR LED); 2 (Warm light)

Angle Adjustment Pan: 0° to 352°;

Tilt: 0° to 90°

Lens Type Fixed-focal

Focal Length 6 mm

Max. Aperture F1.6

Field of View H: 49°; V: 26°; D: 57°

Intelligence

Human Detection Yes

Vehicle Detection Yes

Audio and Video

Video Compression H.265

Video Frame Rate Main stream: 2880 × 1620@15 fps

sub stream: 640 × 360@15 fps

*The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

Video Bit Rate H.265: 768 kbps–4096 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Motion Detection Yes

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic

Built-in Speaker Yes, built-in speaker

Audio Compression	G.711a
Network	
Network Port	RJ-45 (10/100 Base-T)
Wi-Fi	IEEE 802.11b/g/n/ax 2.412-2.472 GHz, 2.4G, ≤20dBm@2400-2483.5MHz
Wi-Fi Pairing	Bluetooth pairing
Storage	Micro SD card (support max. 256 GB)
Management Software	DMSS
Mobile Client	iOS; Android
General	
Certifications	CE
Power Supply	12 VDC
Power Consumption	Basic: 2.6 W Max.: 10.6 W (pulling stream+ IR + siren and light active deterrence)
Operating Temperature	-20 °C to +50 °C (-4 °F to +122 °F)
Operating Humidity	≤95% (RH), non-condensing
Protection	IP66
Casing Material	Plastic
Product Dimensions	159.4 mm × 119.1 mm × 210 mm (6.28" × 4.69" × 8.27") (L × W × H)
Net Weight	585 g (1.29 lb)