DAHUA

DH-PFM800-4K

Kod: 00-00001183 · Başlıqlar və Konnektorlar



DAHUA DH-PFM800-4K 1-CH PASSIVE VIDEO BALUN; Real-time transmission over UTP CAT5E/6 cable; Passive, no need for power supply; Excellent anti-thunder, anti-static and anti-interference capabilities; Compatible format: HDCVI/TVI/AHD/CVBS; With female BNC connector, and pluggable screw terminal connections.

Texniki göstəricilər

Tip	BNC

Ətraflı məlumat

Technical Specification				
Model	DH-PFM800-4K			
Properties				
Transmission Signal	1-CH			
Network cable Type	UTP CAT5E/6 (material: CU)			
Transmission Properties	HDCVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M/4K : max.200m (656.17ft)
	TVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)
	AHD	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)
Video Transmission Properties				
Coaxial Video Connector	BNC-M			
Connection Way	RJ45			
Compatible Format	HDCVI/TVI/AHD/CVBS			
Resolution	720P/1080P/4MP/5MP/4K			
Protection				
ESD	1a contact discharge electricity level 3			
	1b air discharge electricity level 3			
	Per: IEC61000-4-2			
UTP Cable Connector	2KV(different-mode), 4KV(common-mode)			
	Per: IEC61000-4-5			

Impedance	
BNC Male Impedance	75 ohms
UTP Cable Impedance	100 ohms
Physical Properties	
Weight	40g (0.09lb) (1 pair)
Dimension(LxWxH)	173.8mmx19.5mmx21mm (6.84”x0.77“x0.83”)
Shell	ABS
Color	Black
Environmental	
Operating Temperature	-30℃~+70℃(-22℉~+158℉)
Operating Humidity	<95% RH
Storage Temperature	-40℃~+80℃(-40℉~+176℉)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az