

DH-PFM800-4K

DAHUA DH-PFM800-4K 1-CH PASSIVE VIDEO BALUN; Real-time transmission over UTP CAT5E/6 cable; Passive, no need for power supply; Excellent anti-thunder, anti-static and anti-interference capabilities; Compatible format: HDCVI/TVI/AHD/CVBS; With female BNC connector, and pluggable screw terminal connections.



Model	DH-PFM800-4K
Brend	Dahua
Tip	BNC

Specification

Technical Specification				
Model	DH-PFM800-4K			
Properties				
Transmission Signal	1-CH			
Network cable Type	UTP CAT5E/6 (material: CU)			
Transmission Properties	HDCVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M/4K : max.200m (656.17ft)
	TVI	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)

AHD	720P : max.400m (1312.34ft)	1080P : max.250m (820.21ft)	4M/5M : max.200m (656.17ft)
Video Transmission Properties			
Coaxial Video Connector	BNC-M		
Connection Way	RJ45		
Compatible Format	HDCVI/TVI/AHD/CVBS		
Resolution	720P/1080P/4MP/5MP/4K		
Protection			
ESD	1a contact discharge electricity level 3		
	1b air discharge electricity level 3		
	Per: IEC61000-4-2		
UTP Cable Connector	2KV(different-mode), 4KV(common-mode)		
	Per: IEC61000-4-5		
Impedance			
BNC Male Impedance	75 ohms		
UTP Cable Impedance	100 ohms		
Physical Properties			
Weight	40g (0.09lb) (1 pair)		
Dimension(LxWxH)	173.8mmx19.5mmx21mm (6.84"x0.77"x0.83")		
Shell	ABS		
Color	Black		
Environmental			
Operating Temperature	-30~+70(-22~+158)		
Operating Humidity	<95% RH		
Storage Temperature	-40~+80(-40~+176)		