

DAHUA

DH-S3010-8GT-90 10-Port Gigabit Unmanaged PoE Switch

Kod: 00-00001255 · Switchlər



PP12-C5EU-D05 (IKT Cat.5E UTP wall patch panel, 12 ports (IDC Dual)

Texniki göstəricilər



8 Port

Port sayı



1000mb/s

Port sürəti



PoE

PoE

Ətraflı məlumat

Basic

Layer	Unmanaged
Switching Capacity	20 Gbps
Packet Forwarding Rate	14.88 Mpps
Description of Function Slots	Port 1-8: 8 × RJ45 10/100/1000Mbps (PoE) Port 9-10: 2 × RJ45 10/100/1000Mbps (Uplink)
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Temperature	-40 °C to +75 °C (-40 °F to +167 °F)
Storage Humidity	5%–95% (RH), non-condensing
Power Supply	External power supply: 53 V, 50/60 Hz, max 1.81 A
Power Consumption	Idling: 2.2 W Full load: 97.5 W
Statics Protection	Air discharge: 8 kV Contact discharge: 6 kV
Lightning Protection	Common mode: 6 kV Differential mode: 1 kV
Net Weight	0.3 kg (0.66 lb)
Gross Weight	0.882 kg (1.94 lb)
Product Dimensions	184.6 mm × 77.4 mm × 27 mm (7.27" × 3.32" × 1.06") (L × W × H)
Packaging Dimensions	253 mm × 112 mm × 83 mm (9.96" × 4.41" × 3.27") (L × W × H)
Casing Material	Sheet Metal
Installation	Desktop mount; wall mount
Certifications	CE

PoE

PoE	Yes
-----	-----

PoE Power	Port 1-8≤30 W, total≤90 W
PoE Protocol	IEEE 802.3af; IEEE 802.3at
PoE Pin Assignment	1,2,4,5 (V+),3,6,7,8 (V-)
Long Distance PoE Transmission	Yes

Hardware

DIP Switch	Long Distance PoE: The transmission distance of ports 1-8 can reach up to 250 meters. The negotiation speed can be reduced to 10 Mbps.
-------------------	--

Performance

Packet Buffer Size	1 Mbits
Jumbo Frame	9216 Byte
MAC Table Size	2K
Communication Standard	IEEE802.3; IEEE802.3u; IEEE802.3ab; IEEE802.3x

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az