

DH-S3218-16ET-240

Dahua DH-S3218-16ET-240 – 16 PoE port, 2 uplink və 2 SFP portu olan neidarəolunan (unmanaged) PoE switch-dir. 240W ümumi PoE gücü IP kameralar, access point-lər və digər PoE cihazlarını sabit enerji ilə təmin edir. Yüksək performans, davamlılıq və asan quraşdırma təmin edir.



Specifications

Model	DH-S3218-16ET-240
Brand	Dahua
Port say?	16 Port
PoE	PoE
PoE gücü	250 W
Port sür?ti	100mb/s

KEY FEATURES

Hardware Feature	
Included Power Adapter	Yes
PoE	Yes
Ethernet Port	16
Ethernet Port Speed	10/100 Mbps
Ethernet Port Uplink Speed	10/100/1000 Mbps
Optical Port Uplink Speed	1 Gbps
Description of Function Slots	Port 1-16: 16 × RJ-45 10/100 Mbps; Port 17-18: 2 × RJ-45 10/100/1000 Mbps (Combo); Port 17-18: 2 × SFP 1000 Mbps (Combo)
Power Supply	Built-in power supply: 100-240 VAC, 50/60 Hz, 4 A
Operating Temperature	−10 °C to +55 °C (+14 °F to +131 °F)
Operating Humidity	5%–95% (RH), non-condensing
Storage Temperature	−40 °C to +75 °C (−40 °F to +167 °F)
Storage Humidity	5%–95% (RH), non-condensing
Power Consumption	Idling: ≤6 W ; Full load: 265 W
Performance	
Management Type	No
Switching Capacity	7.2 Gbps
Packet Forwarding Rate	5.36 Mpps
Packet Buffer Size	4 Mbit
Jumbo Frame	15K Byte
MAC Table Size	8 K
Communication Standard	IEEE802.3; IEEE802.3u; IEEE802.3x; IEEE802.3ab; IEEE802.3z
Feature	
PoE Protocol	IEEE802.3af; IEEE802.3at; Hi-PoE; IEEE802.3bt
PoE Power	Port 1-2 ≤ 90 W, Port 3-16 ≤ 30 W, total ≤ 240 W
PoE Pin Assignment	1,2,4,5 (V+),3,6,7,8 (V-)
Long Distance PoE Transmission	Yes
General	
Statics Protection	Air discharge: 8 kV; Contact discharge: 6 kV
Lighting Protection	Common mode: 4 kV; Differential mode: 2 kV
Net Weight	2.35 kg (5.18 lb)
Gross Weight	3.00 kg (6.61 lb)
Product Dimensions	440 mm × 220 mm × 44 mm (17.32" × 8.66" × 1.73") (L × W × H)
Packaging Dimensions	540 mm × 342 mm × 90 mm (21.26" × 13.46" × 3.54") (L × W × H)
Casing Material	Sheet metal
Installation	Rack mount;Desktop mount
Certifications	CE