eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

DAHUA

DH-SD29204T-GH

Kod: 00-00004221 · Kamera



DAHUA DH-SD29204T-GH 2MP 4x Starlight IR PTZ NETWORK KAMERA

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
PTZ Obyektiv	**Mic** Mikrofon
Metal Material	**Outdoor** İş mühiti
LED İşıqlandırma	**30 m** İşıqlandırma məsafəsi
MicroSD Yaddaş	

Ətraflı məlumat

Camera	
Matrix	1/2.7" CMOS
Permission	2 MP
Pixels	1920(H) x 1080(V)
Sensitivity	Color: 0.05 lux @ F1.6, B/W: 0.005 lux @ F1.6
Electronic shutter	1/1-1/30.000 s
Signal to noise ratio	More than 50 dB
Lens	
Lens type	Variofocal
Focal length	f=2.7-11 mm
Optical zoom	4x
Digital zoom	16x
Diaphragm	F1.6-F2.8
Viewing angle	112.5°-39° (Wide-Tele)
Focusing	Auto / Manual
Functions	
Day/Night Mode	Mechanical IR cut filter (ICR)/color/b/w
Digital Noise Reduction	Ultra DNR (2D/3D)
Backlight Compensation	BLC/HLC
Wide dynamic range	WDR
White balance	Auto/Manual, ATW, Indoor, Outdoor
Gain adjustment	Auto/manual
Masking	24 programmable zones

Pan and tilt	
Turning range	0°~360°
Tilt range	0°-90° (auto-flip 180°)
Manual control speed	Horizontal: 0.1°~100°/s, Vertical: 0.1°~60°/s
Preset speed	Horizontal: 100°/s, vertical: 60°/s
Presets	300
PTZ mode	5 templates, 8 routes, auto scan, auto pan
Power Overload Action	Automatically restore to previous preset and lens state
Transition	Activation of preset, scan, route - if there is no command within the specified period
Image	
Video compression	H.264+/H.264/MJPEG
Permission	1080P (1920×1080) / 720P (1280×720) / D1 (704×576 / 704×480) / CIF(352×288 / 352×240)
Frame frequency	Main stream: 1080P (1-25/30 fps), 720P (1-50/60 fps) Sub stream 1: D1 / CIF (1-25/30 fps)
Bitrate	H.264: 448K ~ 8192Kbps, MJPEG: 5120K ~ 10240Kbps
Audio	
Audio compression	G.711a / G.711Mu (32kbps) / PCM (128kbps)
Interface	Built-in microphone
Net	
Ethernet	RJ45 port 10/100 Base-T
Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1 x
Number of users	Up to 20 simultaneously
ONVIF	ONVIF Profile S
Mobile applications	iPhone, iPad, Android, Windows Phone
Interface	
SD card slot	Micro SD memory card up to 128 GB

Are common	
Housing material	Metal
IR illumination range	30 meters
Nutrition	DC 12V, POE
Power consumption	Max. 13 W with IR on.
Working conditions	-30°C ~ +60°C
Humidity	0% ~ 90% no condensation
Dimensions	Φ 132.7 x 116.5 mm
Weight	950 grams

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az