

DH-SD29204T-GH

DAHUA DH-SD29204T-GH 2MP 4x Starlight IR PTZ NETWORK KAMERA



Specifications

Model	DH-SD29204T-GH
Brand	Dahua
Yaxşılaşdırıcı	LED
Yaxşılaşdırıcı məsafəsi	30 m
Yaddaş	MicroSD
Növ	IP
Məqəpəxəl	2 MP
Obyektiv	PTZ
Mikrofon	Mic
Material	Metal
Çalışma mühiti	Outdoor

KEY FEATURES

Camera

Matrix	1/2.7" CMOS
Permission	2 MP
Pixels	1920(H) x 1080(V)
Sensitivity	Color: 0.05 lux @ F1.6, B/W: 0.005 lux @ F1.6
Electronic shutter	1/1-1/30.000 s
Signal to noise ratio	More than 50 dB

Lens

Lens type	Variofocal
Focal length	f=2.7-11 mm
Optical zoom	4x
Digital zoom	16x
Diaphragm	F1.6-F2.8
Viewing angle	112.5°-39° (Wide-Tele)
Focusing	Auto / Manual

Functions

Day/Night Mode	Mechanical IR cut filter (ICR)/color/b/w
----------------	--

Digital Noise Reduction	Ultra DNR (2D/3D)
-------------------------	-------------------

Backlight Compensation

Backlight Compensation	BLC/HLC
------------------------	---------

Wide dynamic range	WDR
--------------------	-----

White balance	Auto/Manual, ATW, Indoor, Outdoor
---------------	-----------------------------------

Gain adjustment	Auto/manual
-----------------	-------------

Masking	24 programmable zones
---------	-----------------------

Pan and tilt

Turning range	0°~360°
---------------	---------

Tilt range	0°-90° (auto-flip 180°)
------------	-------------------------

Manual control speed	Horizontal: 0.1°~100°/s, Vertical: 0.1°~60°/s
----------------------	---

Preset speed	Horizontal: 100°/s, vertical: 60°/s
--------------	-------------------------------------

Presets	300
---------	-----

PTZ mode	5 templates, 8 routes, auto scan, auto pan
----------	--

Power Overload Action	Automatically restore to previous preset and lens state
-----------------------	---

Transition

Transition	Activation of preset, scan, route - if there is no command within the specified period
------------	--

Image

Video compression	H.264+/H.264/MJPEG
-------------------	--------------------

Permission	1080P (1920×1080) / 720P (1280×720) / D1 (704×576 / 704×480) / CIF(352×288 / 352×240)
------------	---

Frame frequency	Main stream: 1080P (1-25/30 fps), 720P (1-50/60 fps) Sub stream 1: D1 / CIF (1-25/30 fps)
-----------------	--

Bitrate	H.264: 448K ~ 8192Kbps, MJPEG: 5120K ~ 10240Kbps
---------	--

Audio**Audio compression** G.711a / G.711Mu (32kbps) / PCM (128kbps)**Interface** Built-in microphone**Net****Ethernet** RJ45 port 10/100 Base-T**Protocols** IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1 x**Number of users** Up to 20 simultaneously**ONVIF** ONVIF Profile S**Mobile applications** iPhone, iPad, Android, Windows Phone**Interface****SD card slot** Micro SD memory card up to 128 GB**Are common****Housing material** Metal**IR illumination range** 30 meters**Nutrition** DC 12V, POE**Power consumption** Max. 13 W with IR on.**Working conditions** -30°C ~ +60°C**Humidity** 0% ~ 90% no condensation**Dimensions** Φ 132.7 x 116.5 mm**Weight** 950 grams