eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

DAHUA

DH-SD49225-HC-LA1

Kod: 00-00002625 · Kamera



DAHUA DH-SD49225-HC-LA1 2Mп 25x Starlight HDCVI PTZ KAMERA

Texniki göstəricilər

Analoq Növ	**2 MP** Meqapixel
PTZ Obyektiv	**2.7 - 13.5mm** Fokus
İR İşıqlandırma	**100m** İşıqlandırma məsafəsi
Metal Material	**Outdoor** İş mühiti
IP66 Qoruma	

Ətraflı məlumat

Camera				
Image Sensor	1/2.8" STARVIS™ CMOS			
Pixel	2MP			
Max. Resolution	1920 (H) x 1080 (V)			
ROM	16 MB			
RAM	256 MB			
Electronic Shutter Speed	1/3 s–1/100000 s			
Scanning System	Progressive			
Min. Illumination	Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0 Lux@F1.6 (IR on)			
Illumination Distance	100 m (328.08 ft)			
Illuminator On/Off Control	Auto/Manual			
Illuminator Number	6			
Lens				
Focal Length	4.8 mm–120 mm			
Max. Aperture	F1.6–F3.5			
Field of View	H: 58.5°–2.8°; V: 33.2°–1.5°; D: 67.5°–3.2°			
Optical Zoom	25x			
Focus Control	Auto/Semi-Auto/Manual			
Close Focus Distance	0.1 m–1.5 m (0.33 ft–4.92 ft)			
Iris Control	Auto/Manual			
DORI Distance	Detect	Observe	Recognize	Identify
	1655.2 m (5430.45 ft)	656.8 m (2154.86 ft)	331.0 m (1085.96 ft)	165.5 m (542.98 ft)

PTZ	
Pan/Tilt Range	Pan: 0°–360°Tilt: -15°–+90°; auto flip 180°
Manual Control Speed	Pan: 0.1°–200°/s; Tilt: 0.1°–120°/s
Preset Speed	Pan: 240°/s; Tilt: 200°/s
Presets	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Scan	5
Speed Adjustment	Support
Power-off Memory	Support
Idle Motion	Preset/Tour/Pattern/Scanning
Protocol	DH-SD Pelco-P/D (auto recognition)
Video	
Resolution	1080P (1920 × 1080); 720P (1280 × 720); D1 (704 × 576/704 × 480)
Frame Rate	1080P (25/30 fps), 720P (25/30/50/60 fps)
Day/Night	Support
BLC	Support
WDR	120 dB
HLC	Support
White Balance	Auto/Indoor/Outdoor/Tracking/Manual/Sodium lamp/Natural light/Street lamp
Gain Control	Auto/Manual
Noise Reduction	2D/3D
Defog	Electronic
Digital Zoom	16x
Flip	0°/180°
Privacy Masking	Up to 24 areas

CVI Product Output Mode	CVI; TVI; AHD; CVBS
Audio	
Compression	G.711a; G.711Mu
Certification	
Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014 UL: UL60950-1+CAN/CSA C22.2, No.60950-1
Port	
Audio Input	1 (LINE IN; bare wire)
Alarm Input	2
Alarm Output	1
Power	
Power Supply	DC 12V/3A ± 10%
Power Consumption	9.6 W 23.2 W (IR light on, PTZ)
Environment	
Operating Temperature	–40°C to +70°C (–40°F to +158°F)
Operating Humidity	≤ 95%RH
Protection	IP66; TVS 6000V lightning protection; surge protection
Structure	
Dimensions	295.4 mm × Φ160.0 mm (11.63" × Φ6.30")
Net Weight	3 kg (6.61 lb)
Gross Weight	4.2 kg (9.26 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az