eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

DAHUA

DH-SD6CE245U-HNI

Kod: 00-00000418 · Kamera



DAHUA DH-SD6CE245U-HNI 2MP 45x Starlight IR PTZ NETWORK KAMERA

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
PTZ Obyektiv	**2.7 - 13.5mm** Fokus
LED İşıqlandırma	**200m** İşıqlandırma məsafəsi
MicroSD Yaddaş	**Outdoor** İş mühiti
IP67 Qoruma	**Metal** Material

Ətraflı məlumat

Model		**DH-SD6CE245U-HNI**	
Camera			
Matrix		1/2.8” STARVIS™ CMOS	
Effective pixels		1920 x 1080	
RAM/ROM		512 M / 128 M	
Scanning system		Progressive	
Electronic shutter speed		1/1 s ~ 1/30,000 s	
Min. lighting		Color: 0.005Lux F1.6; B/W: 0.0005Lux F1.6; 0Lux F1.6 (IR on)	
Signal to noise ratio		More than 55dB	
IR distance		Up to 250 m (820ft)	
IR control on / off		Auto / Manual	
IR LEDs		6	
Lens			
Focal length		3.95mm ~ 177.7mm	
Max. diaphragm		F1.6~F4.95	
Viewing angle		70.3° ~ 1.8°	
Optical zoom		45x	
Focus control		Auto / Manual	
Closed focal length		100mm~1000mm	
DOOR Distance			
Detection	Notification	Recognition	Identification
2345 m (7694ft)	938 m (3077ft)	469 m (1539ft)	234 m (768ft)
PTZ			

Pan/Tilt Range	Panning: 0°~360° infinite; Tilt: -20°~90°, auto rotate 180°
Manual control speed	Pan: 0.1°~200°/s; Tilt: 0.1°~120°/s
Preset speed	Pan: 300°/s; Tilt: 200°/s
Presets	300
PTZ mode	5 Templates; 8 Tours; Auto pan; Auto scan
Speed setting	Human-Centric Focal Length/Speed Adaptation
Enable action	Automatically restore to previous PTZ and lens status after power failure
Driving in standby mode	Activate preset/scan/tour/pattern if there is no command within the specified period
Protocol	DH-SD, Pelco-P/D (automatic recognition)
Intelligent properties	
Trigger Events	Motion detection, video tampering, scene change, network disconnection, IP address conflict, illegal access, storage anomaly
Automatic tracking	Supports
IVS	Stretch / Invasion / Abandoned / Lost objects
Advanced Smart Features	Face recognition, Heatmap
Video	
Compression	H.265+ / H.265 / H.264+ / H.264
Streaming Features	3 streams
Permission	1080P (1920 × 1080) / 720P (1280 × 720) / D1 (704 × 576 / 704 × 480) / CIF (352 × 288 / 352 × 240)
Frame frequency	Main Stream:1080P/1.3M/720P(1~50/60fps)
	Add. stream 1:D1/CIF(1~25/30fps)
	Add. Stream 2: 1080P/1.3M/720P/D1/CIF (1~25/30fps)
Bitrate control	CBR/VBR
Bit rate	H.265/H.264: 448K~8192Kbps

Day Night	Auto (ICR) / Color / B/W
Backlight Compensation	BLC/HLC/WDR (120dB)
White Balance	Auto / ATW / Indoor / Outdoor / Manual
Gain control	Auto / Manual
Noise suppression	Ultra DNR (2D/3D)
Motion Detection	Supports
Area of interest	Supports
Electronic Image Stabilization (EIS)	Supports
Prevent fogging	Supports
Digital zoom	16x
Frame rotation	180°
Privacy mask	Up to 24 zones
Audio	
Compression	G.711a / G.711Mu / AAC / G.722 / G.726 / G.729 / MPEG2-L2
Net	
Ethernet	RJ-45 (10Base-T/100Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP,ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP,DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1 x
Compatibility	ONVIF Profile S&G, API
Streaming Method	Unicast/Multicast
Max. user access	20 users
Storage	NAS (Network Attached Storage), Local PC for instant recording, Micro SD card 256GB
Web browsing	IE, Chrome, Firefox, Safari
Management software	Smart PSS, DSS, DMSS
Smartphones	IOS, Android
Interface	

Video interface	1 port (BNC, 1.0 V [pp], 75 Ohm)
RS485	1
Audio input /out.	eleven
Alarm input /out.	7/2
Protection	
Degree of protection	IP67
Anti-vandal protection	IK10
Environment	
terms of Use	-40°C ~ 70°C (-40°F ~ +158°F) / Less than 95% RH
Electrical properties	
Power supply	AC24V / 3A(±25%), PoE+(802.3at)
Power consumption	17 W 25 W (IR on, heater on)
General information	
Frame	Metal
Color	White
Dimensions	φ209 × 337.4 mm
Net weight	5.8 kg (12.79 lb)
Gross weight	9.1 kg (20.06 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az