

# DH-SD6CE245U-HNI

DAHUA DH-SD6CE245U-HNI 2MP 45x Starlight IR PTZ NETWORK KAMERA



## Specifications

Model	DH-SD6CE245U-HNI
Brand	Dahua
Material	Metal
Qoruma	IP67
Növ	IP
Meqapixel	2 MP
Obyektiv	PTZ
Fokus	2.7 - 13.5mm
??qland?rma	LED
??qland?rma m?saf?si	200m
Yadda?	MicroSD
?? mühiti	Outdoor

KEY FEATURES

<b>Model</b>	DH-SD6CE245U-HNI		
<b>Camera</b>			
<b>Matrix</b>	1/2.8" STARVIS™ CMOS		
<b>Effective pixels</b>	1920 x 1080		
<b>RAM/ROM</b>	512 M / 128 M		
<b>Scanning system</b>	Progressive		
<b>Electronic shutter speed</b>	1/1 s ~ 1/30,000 s		
<b>Min. lighting</b>	Color: 0.005Lux F1.6; B/W: 0.0005Lux F1.6; 0Lux F1.6 (IR on)		
<b>Signal to noise ratio</b>	More than 55dB		
<b>IR distance</b>	Up to 250 m (820ft)		
<b>IR control on / off</b>	Auto / Manual		
<b>IR LEDs</b>	6		
<b>Lens</b>			
<b>Focal length</b>	3.95mm ~ 177.7mm		
<b>Max. diaphragm</b>	F1.6~F4.95		
<b>Viewing angle</b>	70.3° ~ 1.8°		
<b>Optical zoom</b>	45x		
<b>Focus control</b>	Auto / Manual		
<b>Closed focal length</b>	100mm~1000mm		
<b>DOOR Distance</b>			
<b>Detection</b>	<b>Notification</b>	<b>Recognition</b>	<b>Identification</b>
2345 m (7694ft)	938 m (3077ft)	469 m (1539ft)	234 m (768ft)
<b>PTZ</b>			
<b>Pan/Tilt Range</b>	Panning: 0°~360° infinite; Tilt: -20°~90°, auto rotate 180°		
<b>Manual control speed</b>	Pan: 0.1°~200°/s; Tilt: 0.1°~120°/s		
<b>Preset speed</b>	Pan: 300°/s; Tilt: 200°/s		
<b>Presets</b>	300		
<b>PTZ mode</b>	5 Templates; 8 Tours; Auto pan; Auto scan		
<b>Speed setting</b>	Human-Centric Focal Length/Speed Adaptation		
<b>Enable action</b>	Automatically restore to previous PTZ and lens status after power failure		
<b>Driving in standby mode</b>	Activate preset/scan/tour/pattern if there is no command within the specified period		
<b>Protocol</b>	DH-SD, Pelco-P/D (automatic recognition)		
<b>Intelligent properties</b>			
<b>Trigger Events</b>	Motion detection, video tampering, scene change, network disconnection, IP address conflict, illegal access, storage anomaly		
<b>Automatic tracking</b>	Supports		

<b>IVS</b>	<b>Stretch / Invasion / Abandoned / Lost objects</b>
<b>Advanced Smart Features</b>	<b>Face recognition, Heatmap</b>
<b>Video</b>	
<b>Compression</b>	<b>H.265+ / H.265 / H.264+ / H.264</b>
<b>Streaming Features</b>	<b>3 streams</b>
<b>Permission</b>	<b>1080P (1920 × 1080) / 720P (1280 × 720) / D1 (704 × 576 / 704 × 480) / CIF (352 × 288 / 352 × 240)</b>
<b>Frame frequency</b>	<b>Main Stream:1080P/1.3M/720P(1~50/60fps)</b> <b>Add. stream 1:D1/CIF(1~25/30fps)</b>  <b>Add. Stream 2: 1080P/1.3M/720P/D1/CIF (1~25/30fps)</b>
<b>Bitrate control</b>	<b>CBR/VBR</b>
<b>Bit rate</b>	<b>H.265/H.264: 448K~8192Kbps</b>
<b>Day Night</b>	<b>Auto (ICR) / Color / B/W</b>
<b>Backlight Compensation</b>	<b>BLC/HLC/WDR (120dB)</b>
<b>White Balance</b>	<b>Auto / ATW / Indoor / Outdoor / Manual</b>
<b>Gain control</b>	<b>Auto / Manual</b>
<b>Noise suppression</b>	<b>Ultra DNR (2D/3D)</b>
<b>Motion Detection</b>	<b>Supports</b>
<b>Area of interest</b>	<b>Supports</b>
<b>Electronic Image Stabilization (EIS)</b>	<b>Supports</b>
<b>Prevent fogging</b>	<b>Supports</b>
<b>Digital zoom</b>	<b>16x</b>
<b>Frame rotation</b>	<b>180°</b>
<b>Privacy mask</b>	<b>Up to 24 zones</b>
<b>Audio</b>	
<b>Compression</b>	<b>G.711a / G.711Mu / AAC / G.722 / G.726 / G.729 / MPEG2-L2</b>
<b>Net</b>	
<b>Ethernet</b>	<b>RJ-45 (10Base-T/100Base-TX)</b>
<b>Protocol</b>	<b>IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1 x</b>
<b>Compatibility</b>	<b>ONVIF Profile S&amp;G, API</b>
<b>Streaming Method</b>	<b>Unicast/Multicast</b>
<b>Max. user access</b>	<b>20 users</b>
<b>Storage</b>	<b>NAS (Network Attached Storage), Local PC for instant recording, Micro SD card 256GB</b>
<b>Web browsing</b>	<b>IE, Chrome, Firefox, Safari</b>
<b>Management software</b>	<b>Smart PSS, DSS, DMSS</b>
<b>Smartphones</b>	<b>IOS, Android</b>
<b>Interface</b>	
<b>Video interface</b>	<b>1 port (BNC, 1.0 V [pp], 75 Ohm)</b>
<b>RS485</b>	<b>1</b>
<b>Audio input /out.</b>	<b>eleven</b>
<b>Alarm input /out.</b>	<b>7/2</b>
<b>Protection</b>	
<b>Degree of protection</b>	<b>IP67</b>