

DH-XVR1B08-I/T

DAHUA DH-XVR1B08-I/T 8 kanallı Penta-brid video qeydedici (XVR) HDCVI, AHD, TVI, CVBS və IP kameraları dəstəkləyir. H.265+ sıxlaşdırma texnologiyası və SMD Plus (ağıllı hərəkət təyini) funksiyası ilə təhlükəsizliyinizi maksimuma çatdırır. Ev və kiçik obyektlər üçün ideal seçimdir.



Specifications

Model	DH-XVR1B08-I/T
Brand	Dahua
Növ	XVR
Kanal say?	8 kanal
Meqapixel	2 MP
Max HDD say?	1 HDD
Max HDD h?cmi	6 TB

KEY FEATURES

System

Main Processor Industrial-grade processor**Operating System** Embedded Linux**Operating Interface** Web; Local GUI

SMD

SMD Plus by Recorder 8 channels: Secondary filtering for human and vehicle, reducing false alarms caused by leaves, rain and lighting condition change**SMD by Camera** 10 channels

Audio and Video

Analog Camera Input 8 BNC ports, supports HDCVI/AHD/TVI/CVBS auto-detect**Camera Input**
1. CVI: 1080p@25/30 fps; 720p@25/30 fps.
2. TVI: 1080p@25/30 fps; 720p@25/30 fps.
3. AHD: 1080p@25/30 fps; 720p@25/30 fps.**IP Camera Input**
Up to 10 channels of IPC access
2 IP channels by default + 8 channels (analog channels are converted to IP channels)
Incoming bandwidth: 40 Mbps, recording bandwidth: 40 Mbps and outgoing bandwidth: 40 Mbps**Encoding Capacity**
Main stream: the 1st channel 1080N/720p@(1 fps~25/30 fps), others 1080N/720p@(1 fps~15 fps); 960H/D1/CIF@(1 fps~25/30 fps)
Sub stream: CIF@(1 fps~7 fps)**Dual-stream** Yes**Video Bit Rate** 32 kbps~4096 kbps**Audio Sampling** 8 kHz, 16 bit**Audio Bit Rate** 64 kbps**Video Output**
1 HDMI, 1 VGA
HDMI: 1920 × 1080, 1280 × 1024, 1280 × 720
VGA: 1920 × 1080, 1280 × 1024, 1280 × 720**Multi-screen Display**
When IP extension mode not enabled: 1/4/8/9
When IP extension mode enabled: 1/4/8/9/16**Third-party Camera Access** Panasonic; Sony; Hanwha; Axis; Arecont; ONVIF

Compression Standard

Video Compression AI Coding; Smart H.265+; H.265; Smart H.264+; H.264**Audio Compression** G.711a; G.711u; PCM

Network

Network Protocol HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS; SNMP; Alarm Server; P2P; Auto Registration; IP Search (Supports IP camera, DVR, NVS, etc.)**Mobile Phone Access** iOS; Android**Interoperability** ONVIF 25.06 (Profile T; Profile S; Profile G; Profile M); CGI; SDK**Browser** Chrome; IE; Safari; Edge; Firefox

Recording Playback

Record Mode General; alarm; motion detection**Recording Playback** 1/4/9**Backup Method** USB device and network**Playback Mode** Instant playback; general playback; event playback; tag playback; smart playback

Alarm

General Alarm	Motion detection; HDCVI alarm; camera external alarm; network alarm; PIR alarm
Anomaly Alarm	Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline
Intelligent Alarm	SMD Plus
Alarm Linkage	Record; snapshot (panoramic); IPC external alarm output; audio; buzzer; log; preset; email

Ports

Audio Input	1-channel RCA 8-channel BNC (Coaxial Audio)
Audio Output	1-channel RCA
Two-way Talk	Coaxial two-way talk: 8-channel BNC Local and network user two-way talk: Shares the same audio input with the first channel

Disk Interface	1 SATA port, up to 6 TB. This limit varies depending on the environment temperature.
----------------	--

USB	2 (2 rear USB 2.0 ports)
-----	--------------------------

HDMI	1
------	---

VGA	1
-----	---

Network Port	1 (10/100 Mbps Ethernet port, RJ-45)
--------------	--------------------------------------

General

Power Supply	12 VDC, 1.5 A
--------------	---------------

Power Consumption	<7 W (without HDD)
-------------------	--------------------

Net Weight	0.57 kg (1.26 lb)
------------	-------------------

Gross Weight	0.97 kg (2.14 lb)
--------------	-------------------

Product Dimensions	197.0 mm × 204.3 mm × 41.5 mm (7.76" × 8.04" × 1.63") (W × D × H)
--------------------	---

Packaging Dimensions	332.0 mm × 64.0 mm × 240.0 mm (13.07" × 2.52" × 9.45") (W × D × H)
----------------------	--

Operating Temperature	−10 °C to +45 °C (+14 °F to +113 °F)
-----------------------	--------------------------------------

Storage Temperature	−20 °C to +60 °C (−4 °F to +140 °F)
---------------------	-------------------------------------

Operating Humidity	10%–90% (RH), non-condensing
--------------------	------------------------------

Installation	Desktop
--------------	---------

Certifications	CE-LVD: IEC 62368-1:2014 CE-EMC: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55032:2015+A11:2020, EN 55035:2017+A11:2020, EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014
----------------	--