

DAHUA

DHI-ASI6214S

Kod: 00-00005384 · Access Control



DAHUA DHI-ASI6214S Face Recognition Access Controller – inkişaf etmiş AI üz tanıma funksiyası ilə müasir giriş nəzarət cihazıdır. 50,000 üz yaddaşı, kart və şifrə dəstəyi, IP65 qoruma dərəcəsi və sürətli identifikasiya ilə müəssisələr üçün ideal təhlükəsizlik həllidir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](https://eurotechnology.az/product/dahua/dhi-asi6214s)
<https://eurotechnology.az/product/dahua/dhi-asi6214s>

Texniki göstəricilər

	Controller Cihaz tipi		IC Kart tipi
	Lan Qoşulma		10000 Kart sayı
	6000 Üz tanıma		IP65 Qoruma

Ətraflı məlumat

System	
Main Processor	Embedded Processor
Button Type	Touch button
Network Protocol	UDP; TCP; IPv4; RTSP; SIP; P2P; RTP
OSDP Protocol	Yes
Interoperability	CGI; ONVIF
SDK and API	Yes
Basic	
Product Type	Standalone
Display Screen	4.3" LCD
Screen Type	Capacitive Touchscreen
Screen Resolution	272 (H) × 480 (V)
Camera	2-MP CMOS HD dual-lens camera
WDR	DWDR
Light Compensation	Auto IR
Voice Prompt	Yes
Buzzer	Yes
Casing Material	PC+GF
Function	
Unlock Mode	Fingerprint, Card, remote, password, QR code, face and combination unlock
Card Type	IC cards
Period List	128 periods
Holiday Period	128 periods
Network Update	Yes
First User Unlock	Yes
Remote Verification	Yes

Restricted List/Trusted List	Yes
Peripheral Card Reader	1 × RS-485 card reader 1 × Wiegand card reader
Multi-user Authentication	Yes
Real-time Monitoring	Yes
Multi-factor Authentication	Yes
Capture Function	Yes
Web Configuration	Yes
Auto Registration	Yes
Performance	
Card Reading Distance	0 cm–3 cm (0"–1.18")
Face Recognition Height Range	1.1 m–2.0 m (3.61 ft–6.56 ft)
Face Recognition Distance	0.3 m–1.5 m (0.98 ft–4.92 ft)
Face Recognition Accuracy	99.9%
Face Recognition Time	0.2 s
Fingerprint Verification Mode	1:N
User	
User (Card) Type	Normal user; VIP users; patrol users; guest user; blocklist user; other user; custom user 1; custom user 2
Capacity	
User Capacity	6,000
Face Image Capacity	6,000
Card Capacity	10,000
Password Capacity	6,000
Record Capacity	300,000
Port	
RS-485	1
Wiegand	1

USB	1
Network Port	1 × RJ-45 10/100 Mbps self-adaptive Ethernet port
Alarm Input	1
Alarm Output	1
Alarm Linkage	Yes
Exit Button	1
Door Status Detection	1
Lock Control	1
Alarm	
Anti-pass Back	Yes
Tamper Alarm	Yes
Duress Alarm	Yes
Door Sensor Timeout	Yes
Intrusion	Yes
Illegal Card Exceeding Threshold	Yes
Duress Fingerprint	Yes
General	
Power Adapter	Included
Power Supply	12 VDC, 1.5 A
Protection	IP65
Power Consumption	≤12 W
Product Dimensions	180.1 mm × 90.1 mm × 27.0 mm (7.09" × 3.55" × 1.06") (L × W × H)
Packaging Dimensions	268 mm × 136 mm × 78 mm (10.55" × 5.35" × 3.07") (L × W × H, in an inner carton) 590 mm × 432 mm × 302 mm (23.23" × 17.01" × 11.89") (L × W × H, protection box)
Operating Temperature	-30 °C to +60 °C (-22 °F to +140 °F)
Operating Humidity	0%–90% (RH), non-condensing
Operating Altitude	0 m–1,300 m (0 ft–4265.09 ft)

Operating Environment	Outdoor; Indoor
Gross Weight	0.70 kg (1.54 lb)
Accessory	Wall mount bracket (included)
Installation	Turnstile mount; 86 case mount; wall mount; surface mount

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az