

DHI-ASR2100A-D

DAHUA DHI-ASR2100A-D Access Reader - RFID oxuyucu, 125kHz ID kart dəstəyi ilə effektiv və təhlükəsiz giriş idarəetməsi təmin edir. RS485 və Wiegand interfeysləri sayəsində bir çox sistemlərlə integrasiya oluna bilər. Daxili və xarici istifadəyə uyğundur.



Specifications

Model	DHI-ASR2100A-D
Brand	Dahua
Cihaz tipi	Reader
Kart tipi	ID
Qoruma	IP66

KEY FEATURES

Category	Specification
Basic	
Product Type	Card reader
Buzzer	Yes
Casing	PC/acrylic panel
Function	
Unlock Mode	Card swiping
Card Type	ID card
Performance	
Response Time	0.1 s
Reading Distance	0 cm–5 cm (0"–1.97")
Port	
RS-485	1 channel
Wiegand	1 output channel
Alarm	
Tamper Alarm	Yes
General	
Power Supply	12V 0.5A DC
Protection	IP66 (silicon sealant is needed, see the manual)
Power Consumption	Standby ≤ 0.9W, Working ≤ 1.7W
Product Dimensions	123 mm × 86 mm × 15 mm (4.84" × 3.38" × 0.59")
Packaging Dimensions (inner carton)	185 mm × 163 mm × 71 mm (7.28" × 6.41" × 2.80")
Packaging Dimensions (carton)	578 mm × 383 mm × 349 mm (22.76" × 15.08" × 13.74")
Operating Temperature	–30°C to +70°C (–22°F to +158°F)
Operating Humidity	5%RH–95% (non-condensing)
Operating Environment	Indoor; outdoor
Gross Weight	0.35 kg (0.77 lb)
Installation	Surface mount
Certifications	CE; FCC