

DHI-ASR2100H

DAHUA DHI-ASR2100H Access Reader - IC kart dəstəkləyən RFID oxuyucudur. IP66 səviyyəli qorunma ilə açıq havada da istifadəyə uyğundur. RS485 və Wiegand interfeysləri vasitəsilə müxtəlif giriş sistemləri ilə asanlıqla inteqrasiya olunur.



Specifications

Model	DHI-ASR2100H
Brand	Dahua
Cihaz tipi	Reader
Kart tipi	IC
Qoruma	IP66

KEY FEATURES

System	
OSDP Protocol	Yes
Basic	
Product Type	Card reader
Buzzer	Yes
Casing Material	PC + ABS
Function	
Unlock Mode	Card
Card Type	IC card
Performance	
Response Time	0.1 s
Card Reading Distance	0 cm–8cm (0"–3.15")
Port	
RS-485	1
Wiegand	1 channel output
Alarm	
Tamper Alarm	Yes
General	
Power Supply	12 VDC, 0.5 A
Protection	IP66
Power Consumption	≤ 0.48 W (standby), ≤ 1.2 W (working)
Product Dimensions	127 mm × 46 mm × 20 mm (5.00" × 1.81" × 0.79")
Packaging Dimensions	139 mm × 73 mm × 48 mm (5.47" × 2.87" × 1.89")
Operating Temperature	–30 °C to +70 °C (–22 °F to +158 °F)
Operating Humidity	≤ 95% (RH)
Operating Environment	Outdoor
Gross Weight	104 g (0.23 lb)
Installation	Surface Mount