

DHI-KTA02M

DAHUA DHI-KTA02M VIDEO INTERCOM KIT



Model	DHI-KTA02M
Brend	Dahua
Bağlantı tipi	Analoq
Cihaz	KİT
Material	Plastik

Specification

DHI-VTH1020J	
System	
Button Type	Touch keypad
Basic	
Display	7.0" TFT
Resolution	1024 × 600
Indicator Light	1 indicator light; Green: Power on
Function	
Communication Method	Analog
Performance	
Casing	PC + ABS
General	
Color	White
Power Supply	DC 12V/1A
Power Adapter	Included
Installation	Surface mount
Certifications	CE/FCC
Accessory	Bracket (included)
Dimensions	133.90 mm × 182.70 mm × 17.70 mm (5.27" × 7.19" × 0.70")
Operating Temperature	-10°C to +55°C (+14°F to +131°F)
Operating Humidity	10%RH–95%RH
Power Consumption	≤ 2W (standby) ≤ 5W (working)

Net Weight	0.25 kg (0.55 lb)
Gross Weight	0.48 kg (1.05 lb)
DHI-VTO1000JM	
System	
Button Type	Mechanical
Basic	
Camera	1/4" 1.3 MP CMOS
Field of View	Horizontal: 70° Vertical: 40°
WDR	DWDR
Illuminator Type	Auto IR
Day/Night	ICR auto switch
Audio Input	1 channel to the microphone; pickup distance 0.5 m
Audio Output	1 channel to the speaker
Indicator Light	1 indicator light; Green: Power on
Function	
Communication Method	Analog
Unlock Mode	Remote unlock
Performance	
Casing	ADC12
Port	
Unlock Button	1
Door Status Detection	1
General	
Color	Black
Power Supply	Powered by indoor monitor
Installation	Surface mount
Certifications	CE/FCC
DHI-VTO1000JM	
Accessory	Rain cover (included)
Dimensions	131.45 mm × 46.00 mm × 33.80 mm (5.18" × 1.81" × 1.33")
Protection Grade	IP66 (Apply silicon sealant to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)
Operating Temperature	-30°C to +60°C (-22°F to +140°F)
Operating Humidity	10%RH–95%RH
Power Consumption	≤ 1W (standby) ≤ 3W (working)
Net Weight	0.18 kg (0.40 lb)
Gross Weight	0.40 kg (0.84 lb)