

DAHUA

DHI-NVR2108HS-8P-4KS2

Kod: 00-00000302 · Videoregistrator



DAHUA NVR2108HS-8P-4KS2 8 kanallı 4K IP video qeydedici (NVR) daxili 8 PoE portu ilə quraşdırılmanı maksimum asanlaşdırır. Smart H.265+ texnologiyası və 8MP-ə qədər təsvir dəstəyi ilə təhlükəsizlik sisteminizi ən yüksək səviyyəyə çatdırın.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)

<https://eurotechnology.az/product/dahua/dhi-nvr2108hs-8p-4ks2>

Texniki göstəricilər



NVR

Növ



8 kanal

Kanal sayı



PoE

PoE dəstəyi



8 MP

Meqapixel



1 HDD

Max HDD sayı



10 TB

Max HDD həcmi

Ətraflı məlumat

System	
Main Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Audio and Video	
IP Camera Input	8 Channel
Two-way Talk	1 Channel Input, 1 Channel Output, RCA
Display	
Interface	1 HDMI, 1 VGA
Resolution	HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720
	VGA: 1920×1080, 1280×1024, 1280×720
Decoding Capacity	1ch@8MP 30fps, 4ch@1080P 30fps
Multi-screen Display	1/4/8/9
OSD	Camera title, Time, Camera lock, Motion detection, Recording
Recording	
Compression	Smart H.265+/H.265/Smart H.264+/H.264
Resolution	8MP/6MP/5MP/4MP/3MP/1080P/ 720P/ D1&etc.
Record Rate	80Mbps
Bit Rate	16Kbps ~ 20Mbps Per Channel
Record Mode	Manual, Schedule (Continuous, MD (Motion Detection), Alarm, IVS)
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Video Detection and Alarm	

Trigger Events	Recording, PTZ, Tour, Video Push, Snapshot, and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), and Tampering
Alarm input	N/A
Relay Output	N/A
Playback and Backup	
Sync Playback	1/4
Search Mode	Time /Date, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network
Third-party Support	
Third-party Support	Onvif, RTSP
Network	
Interface	1 RJ-45 port (10/100/1000Mbps)
PoE	8 ports (IEEE802.3at/af)
Network Function	HTTP/HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, NTP, DHCP, DNS, IP Filter, DDNS, IP Search(Support Dahua IP camera, DVR, NVS and etc.), P2P
Optical Fiber Interface	N/A
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF 2.4, SDK, CGI
Storage	

Internal HDD	1 SATA III port, up to 10 TB for a single HDD. The maximum HDD capacity varies with environment temperature
HDD Mode	Single
eSATA	N/A
Auxiliary Interface	
USB	2 ports (1 Rear USB2.0, 1 Front USB2.0)
RS232	N/A
RS485	N/A
Electrical	
Power Supply	Single, DC48V/2A
Power Consumption	NVR: <5.8W (without HDD) PoE: Max 25.5w for single port, 80w in total
Environmental	
Operating Conditions	-10°C to +55°C (+14°F to +131°F), 86-106kpa
Storage Conditions	0°C to +40°C (+32°F to +104°F), 30-85% RH
Construction	
Dimensions(W×D×H)	Compact 1U, 260 mm × 224.9 mm × 47.6 mm (10.2" × 8.9" × 1.9")
Net Weight	0.8 kg (1.76 lb) (without HDD)
Gross Weight	1.6 kg (3.53 lb) (without HDD)
Certifications	
CE	EN55032, EN55024, EN50130-4, EN60950-1
FCC	Part 15 Subpart B, ANSI C63.4-2014
UL	UL60950-1

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az