DAHUA

DHI-NVR2204-P-I2

Kod: 00-00006344 · Videoregistrator



Dahua DHI-NVR2204-P-I2, 4 ədəd daxili PoE portuna malik 4 kanallı WizSense NVR şəbəkə video qeydiyyatçısıdır. Üz tanıma, SMD Plus və Perimetr Mühafizəsi kimi süni intellekt funksiyaları, 12MP görüntü dəstəyi və 2 HDD yuvası ilə kiçik və orta obyektlər üçün mükəmməl təhlükəsizlik həllidir.

Texniki göstəricilər

NVR Növ	**4 kanal** Kanal sayı
PoE PoE dəstəyi	**12 MP** Meqapixel
2 HDD Max HDD sayı	**10 TB** Max HDD həcmi

Ətraflı məlumat

Feature	Details
Brand	Dahua
Model	DHI-NVR2204-P-I2
Product Type	4-Channel 1U 2HDDs 4PoE WizSense Network Video Recorder (NVR)
IP Camera Input	**4 Channels**
PoE Ports	**4 × PoE Ports** (IEEE 802.3af/at, Max. 25.5W per port, Total 36W)
Incoming / Recording Bandwidth	**80 Mbps** (AI disabled) / **64 Mbps** (AI enabled)
Max. Recording Resolution	Up to **12 MP** (12MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080p / 720p)
Decoding Capability	1-ch @ 12MP (30 fps) or 1-ch @ 8MP (30 fps) or 4-ch @ 1080p (30 fps)
AI by Recorder	1-ch Face Detection & Recognition (up to 10 face databases with 5,000 images); 1-ch Perimeter Protection; 4-ch SMD Plus
AI by Camera	Face Detection & Recognition, Perimeter Protection, SMD Plus
Video Compression	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG
Video Outputs	1 × HDMI (up to 3840 × 2160), 1 × VGA (up to 1920 × 1080) — Simultaneous
Audio I/O	1 × RCA Input / 1 × RCA Output (Two-way Talk)
Alarm I/O	4 × Alarm Inputs / 2 × Alarm Outputs
Storage Interface	**2 × SATA Ports**, up to **10 TB** capacity per HDD (20 TB total)
Network Interface	1 × RJ-45 10/100 Mbps Self-Adaptive Ethernet Port
USB Interfaces	2 × USB 2.0 Ports (1 Front, 1 Rear)
Protocol & Compatibility	ONVIF (Profile T / Profile S / Profile G), CGI, SDK
Power Supply	100–240 VAC, 47–63 Hz (Max. 10W without HDD, excluding PoE)
Dimensions (W × D × H)	1U: 375.0 × 282.9 × 53.0 mm

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az