DHI-VTH5221DW-S2

DAHUA - DHI-VTH5221DW-S2 Wi-Fi Indoor Monitor, 7 düymlük sensor ekranlı IP & Wi-Fi daxili monitorudur. İki tərəfli audio/video zəng, qapı açma funksiyası və Dahua smart ev sistemləri ilə inteqrasiya imkanı təqdim edir. Ev və ofislər üçün müasir, etibarlı və funksional seçimdir.

Specifications

Model	DHI-VTH5221DW-S2
Brand	Dahua
Ba?lant? tipi	IP
Cihaz	Monitor
WIFI	WIFI
Yadda?	SD Card
Material	Plastik
PoE	PoE

KEY FEATURES

System	
Main Processor	Embedded Processor
Operating System	Embedded Linux OS
Interoperability	ONVIF
Network Protocol	IPv4, RTSP, RTP, TCP, UDP, SIP

Basic	
Screen Type	Capacitive Touchscreen
Display Screen	7" TFT
Screen Resolution	1024 (H) × 600 (V)
Audio Compression	G.711a; G.711u; PCM
Audio Input	1
Audio Output	Built-in speaker
Audio Mode	Two-way audio
Audio Enhancement	Echo suppression
Audio Bit Rate	16 KHz, 16 bit

Function	
Communication Mode	Full digital
Information Release	Receive and view text information released by the management center
Leave Videos	Yes (SD card inserted in VTH is needed)
Number of Extensions	Villa: 9
	Apartment: 4
	Wi-Fi intercom: 1 main monitor, 2 extension monitors
Wi-Fi	Yes
Wireless Standard	IEEE802.11b/802.11g/802.11n
Wireless Frequency Range	2.4 GHz
Storage	8 GB Micro SD card (max SD card capacity supported is 64 GB)

Port	
RS-485	1
Alarm Input	6
Door Bell	Yes
Network Port	1 × RJ-45 , 10M/100Mbps self-adaptive port

Performance	
Casing Material	PC + ABS

General	
Appearance Color	White
Power Supply	12 VDC, 1 A
	Standard PoE
Power Adapter	Optional
Installation	Surface Mount
Certifications	CE; FCC; UL
Accessory	Bracket (included)
	Alarm ribbon cable (included)
Product Dimensions	214.0 mm × 140.5 mm × 23.4 mm (8.43" × 5.53" × 0.92")

Operating Temperature	−10 °C to +55 °C (+14 °F to 131 °F)
Operating Humidity	10%–90% (RH), non-condensing
Operating Altitude	Beneath 3,000 m (9,842.52 ft)
Power Consumption	≤3W (standby), ≤7W (working)
Gross Weight	0.69 kg (1.52 lb)
Anti-corrosion Level	Basic Protection