

DS-2AE4225TI-D

DS-2AE4225TI-D 2mp 1080P CMOS Image Sensor 23X Optical Zoom KAMERA HIKVISION

| | |
|-----------------------|----------------|
| Model | DS-2AE4225TI-D |
| Brend | Hikvision |
| İşıqlandırma | İR |
| Material | Metal |
| Növ | Analoq |
| Meqapixel | 2 MP |
| Obyektiv | PTZ |
| İşıqlandırma məsafəsi | 100m |
| Qoruma | IP66 |
| İş mühiti | Outdoor |



Specification

| | |
|---------------------------|--|
| Camera | DS-2AE4225TI-D |
| Matrix: | 1/2.8" Progressive Scan CMOS |
| Frame frequency: | 50Hz: 25 fps (1920x1080) |
| Minimum illumination | F1.6, AGC on: Color: 0.005 Lux, B/W: 0.001 Lux, 0 Lux with IR |
| Effective pixels | 1920(H)x1080(V) |
| White balance | Auto/Manual/ATW/Indoor/Outdoor |
| A.G.C. | Auto/manual |
| WDR | ≥ 120dB |
| Holding time: | 1/1-1/10,000 s |
| Day Night | IR filter |
| Private masks: | 8 customizable private zones |
| Focus control | Auto / semi-automatic / manual |
| DNR | 3D DNR |
| Digital zoom | 16x |
| Lens | |
| Focal length: | 4.8-120mm, 25x |
| Increase rate: | 3.2 s (Wide-Tele) |
| Viewing Angles: | 57.6°-2.5° (Wide-Tele) |
| Minimum working distance: | 10-1500mm (Wide-Tele) |
| Aperture Range: | F1.6~F3.5 |
| Pan/Tilt | |
| Panorama range: | 360° |
| Panning speed: | Manual: 0.1°~80°/s, Preset: 80°/s |
| Tilt angles: | -15°-90° (Auto flip) |
| Tilt speed: | Manual: 0.1°~80°/s, Preset: 80°/s |
| Proportional Zoom: | The rotation speed can be adjusted automatically according to the zoom ratio |

| | |
|-----------------------------|--|
| Number of presets: | 256 |
| Patrol: | 10 routes, up to 32 presets per route |
| Templates: | 5 templates, with a recording time of at least 10 minutes per template |
| Recovering from power loss: | Supported |
| Reaction to an event | Preset / Route / Pattern / Panoramic Scan / Tilt Scan / Selective Scan / Single Frame Scan |
| PTZ display position: | on/off |
| Freeze: | Supported |
| Scheduled tasks | Preset output/patrol/pattern/panoramic scanning/pan/tilt scanning |
| IR illumination | |
| IR range | Up to 100 meters |
| IR illumination intensity | Auto, depends on zoom factor |
| Interfaces | |
| Turbo HD output: | 1 turbo HD 1080p, 1 CVBS output, (composite NTSC or PAL, BNC) |
| RS-485 | Half duplex, adaptive HIKVISION, Pelco-P, Pelco-D |
| UTC functions | UTC (or HIKVISION-C protocol in previous DVR) |
| Basic | |
| Menu language | English |
| Nutrition: | DC 12V |
| Consumption: | Max. 20 W |
| Temperature/humidity: | -30°C-65°C/up to 90% |
| Protection levels: | IP66 TVS 4,000V lightning protection, surge protection |
| Dimensions: | 164.5x295 mm |
| Weight: | 2 kg |