

DS-2CD1023G2-I

DS-2CD1023G2-I 4mm 2mp IR 30m Human Detection Bullet IP Kamera Hikvision

Model	DS-2CD1023G2-I
Brend	Hikvision
Növ	IP
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	4
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik



Specification

Camera	
Image Sensor	1/2.9" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Min. Illumination	Color: 0.01Lux @ (F2.0, AGC ON),B/W: 0 Luxwith IR
Shutter Time	1/3 s to 1/100,000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°,tilt: 0° to 90°, rotate:0° to 360°
Lens	
Lens Type	Fixed focallens, 2.8 and 4mm optional
Focal Length& FOV	2.8 mm, horizontal FOV 104°, vertical FOV 58°, diagonal FOV 123° 4 mm, horizontal FOV 81°, vertical FOV 43°, diagonal FOV 96°
Lens Mount	M12
Iris Type	Fixed
Aperture	F2.0
DORI	
DORI	2.8 mm, D: 42 m, O: 16 m, R: 8 m, I: 4 m 4 mm, D: 57 m, O: 22 m, R: 11 m, I: 5 m
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 30 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	

Main Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 720)
Sub-Stream	50 Hz: 25 fps (640 × 480, 640 × 360) 60 Hz: 30 fps (640 × 480, 640 × 360)
Video Compression	Main stream:H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbpsto 8 Mbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR/VBR
Region of Interest (ROI)	1 fixedregion for mainstream
Audio	
Audio Type	-U: Monosound
Environment Noise Filtering	-U: Yes
Audio Sampling Rate	-U: 8 kHz/16 kHz
Audio Compression	-U: G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio BitRate	-U: 64 Kbps (G.711ulaw)/64 Kbps (G.711alaw)/ 16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps(AAC-LC)
Network	
Security	Password protection, complicated password, watermark, IP address filter, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, hostauthentication (MAC address)
Simultaneous LiveView	Up to 6 channels
API	Open Network Video Interface (Profile S, Profile T, Profile G (only -F model supports)), ISAPI, SDK
Protocols	TCP/IP, ICMP,DHCP, DNS, HTTP,RTP, RTSP, NTP, IGMP, IPv6,UDP, QoS, FTP,SMTP
User/Host	Up to 32 users 3 user levels: administrator, operator, and user
Client	iVMS-4200, Hik-Connect
Web Browser	Plug-in required live view: IE 10, IE 11 Local service: Chrome 57.0+, Firefox 52.0+
Image	
Wide DynamicRange (WDR)	Digital WDR
SNR	≥ 52 dB
Day/Night Switch	Day, Night,Auto, Schedule
Image Enhancement	BLC, HLC,3D DNR
Image Settings	Rotate mode,saturation, brightness, contrast, sharpness, gain, whitebalance, adjustable by client software or web browser

Privacy Mask	4 programmable polygon privacy masks
Interface	
Ethernet Interface	1 RJ45 10 M/100M self-adaptive Ethernet port
On-Board Storage	-F: Built-in memory card slot, support microSD/ microSDHC/microSDXC card, up to 256 GB
Built-in Microphone	-U: Yes
Reset Key	-F: Yes
Event	
Basic Event	Motion detection (support alarm triggering by specified target types (human and vehicle)), videotampering alarm, exception
Linkage	Upload to FTP/memory card(-F), send email ,notify surveillance center, trigger recording (-F), trigger capture
General	
Power	12 VDC \pm 25%, 0.4 A, max. 5 W, \varnothing 5.5 mm coaxial powerplug PoE: 802.3af, Class 3, 36 V to 57 V, 0.2 A to 0.15A, max. 6.5 W
Material	Metal & Plastic
Dimension	170.8 mm \times 66 mm \times 69.1 mm (6.7" \times 2.6" \times 2.7")
Package Dimension	216 mm \times 121 mm \times 118 mm (8.5" \times 4.8" \times 4.6")
Weight	-I: Approx. 265 g (0.6 lb.); -IUF: Approx. 285 g (0.6 lb.)
With Package Weight	-I: Approx. 495 g (1.1 lb.); -IUF: Approx. 510 g (1.1 lb.)
Storage Conditions	-30 °C to 60 °C (-22°F to 140°F). Humidity 95% or less(non-condensing)
Startup and Operating Conditions	-30 °C to 60 °C (-22°F to 140 °F). Humidity 95% or less(non-condensing)
Language	English, Ukrainian
General Function	Heartbeat, anti-banding, mirror, password protection, password reset via email
Approval	
EMC	FCC: 47 CFR Part15, Subpart B CE-EMC: EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4: 2011 +A1: 2014 RCM: AS/NZS CISPR32: 2015 IC: ICES-003: Issue 7 KC: KN32: 2015, KN35:2015
Safety	UL: UL 62368-1 CB: IEC 62368-1: 2014+A11 CE-LVD: EN 62368-1: 2014/A11: 2017 BIS: IS 13252 (Part1): 2010/IEC 60950-1: 2005
Environment	CE-RoHS: 2011/65/EU WEEE: 2012/19/EU Reach: Regulation (EC) No 1907/2006
Protection	IP67: IEC 60529-2013