

DS-2CD1023G2-LIU

DS-2CD1023G2-LIU 2.8MM 2 MP Smart Hybrid Light Fixed Bullet Network Camera

Model	DS-2CD1023G2-LIU
Brend	Hikvision
İş mühiti	Outdoor
Növ	IP
Meqapixel	2 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	30 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP66
Material	Plastik



Specification

Camera	
Image Sensor	1/2.9" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Min. Illumination	Color: 0.005 Lux @ (F1.6,AGC ON), B/W: 0 Lux withIR
Shutter Time	1/3 s to 1/100,000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 90°, rotate:0° to 360°
Lens	
Lens Type	Fixed focallens, 2.8 and 4 mm optional
Focal Length& FOV	2.8 mm, horizontal FOV 103°, vertical FOV 56°, diagonal FOV 121° 4 mm, horizontal FOV 83°, vertical FOV 44°, diagonal FOV 99°
Lens Mount	M12
Iris Type	Fixed
Aperture	F1.6
DORI	
DORI	2.8 mm, D:45 m, O: 18 m, R: 9 m, I: 4 m 4 mm, D: 56 m, O: 22 m, R:11 m, I: 5 m
Illuminator	
Supplement LightType	IR, WhiteLight
Supplement LightRange	Up to 30 m

Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	
Main Stream	50 Hz: 25 fps (1920 × 1080, 1280 × 720) 60 Hz: 30 fps (1920 × 1080, 1280 × 720)
Sub-Stream	50 Hz: 25 fps (640 × 480, 640 × 360) 60 Hz: 30 fps(640 × 480,640 × 360)
Video Compression	Main stream: H.265+/H.265/H.264+/H.264, Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile, MainProfile, High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR, VBR
Region of Interest (ROI)	1 fixed region for main stream
Audio	
Audio Type	Mono sound
Environment NoiseFiltering	Yes
Audio Sampling Rate	8 kHz/16 kHz
Audio Compression	G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio Bit Rate	64 Kbps (G.711 ulaw)/64 Kbps (G.711 alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC)
Network	
Security	Password protection, complicated password, watermark, basic and digest authentication forHTTP, WSSE and digest authentication for Open Network Video Interface, securityaudit log, hostauthentication (MAC address)
Simultaneous Live View	Up to 6 channels
API	Open Network VideoInterface (Profile S, Profile T, Profile G (only -F model supports)), ISAPI, SDK
Protocols	TCP/IP, ICMP, DHCP,DNS, HTTP, RTP, RTSP, RTCP,NTP, IGMP, IPv4,IPv6, UDP, QoS, FTP, SMTP
User/Host	Up to 32 users 3 user levels: administrator, operator, and user
Client	iVMS-4200, Hik-Connect
Web Browser	Plug-in required live view: IE 10, IE11, Local service: Chrome 57.0+, Firefox 52.0+
Image	
Wide DynamicRange (WDR)	Digital WDR
SNR	≥ 52 dB
Day/Night Switch	Day, Night, Auto,Schedule
Image Enhancement	BLC, HLC, 3D DNR

Image Settings	Rotate mode,saturation, brightness, contrast, sharpness, gain, whitebalance, adjustable by client software or web browser
Privacy Mask	4 programmable polygon privacy masks
Interface	
Ethernet Interface	1 RJ45 10 M/100M self-adaptive Ethernet port
On-Board Storage	-F: Built-in memorycard slot, support microSD/microSDHC/microSDXC card,up to 512 GB
Built-in Microphone	Yes
Reset Key	-F: Yes
Event	
Basic Event	Motion detection (support alarm triggering by specified targettypes (human and vehicle)), videotampering alarm, exception
Linkage	Upload to FTP/memory card (-F), sendemail, notify surveillance center, trigger recording (-F),trigger capture
General	
Power	12 VDC \pm 25%, 0.4A, max. 5 W, \varnothing 5.5 mm coaxial powerplug, reverse polarity protection, PoE: IEEE802.3af, Class 3, max. 6.5 W
Material	Metal & Plastic
Dimension	170.8 mm \times 66 mm \times 69.1mm (6.7" \times 2.6" \times 2.7")
Package Dimension	216 mm \times 121 mm \times 118 mm (8.5" \times 4.8" \times 4.6")
Weight	Approx. 265 g (0.6 lb.)
With Package Weight	Approx. 495 g (1.1 lb.)
Storage Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less(non-condensing)
Startup and Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less(non-condensing)
Language	English, Ukrainian
General Function	Heartbeat, anti-banding, mirror,password protection, password reset via email
Approval	
EMC	FCC: 47 CFR Part15, Subpart B, CE-EMC: EN 55032: 2015,EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4: 2011+A1: 2014, RCM: AS/NZSCISPR 32: 2015,IC: ICES-003: Issue7

Safety	UL: UL 62368-1, CB: IEC 62368-1: 2014+A11, CE-LVD: EN 62368-1: 2014/A11: 2017, BIS: IS 13252 (Part1): 2010/IEC 60950-1: 2005
Environment	CE-RoHS: 2011/65/EU, WEEE:2012/19/EU, Reach: Regulation (EC) No 1907/2006
Protection	IP67: IEC 60529-2013