

**HIKVISION****DS-2CD1023G2-LIUF**

Kod: 00-00005647 · Kamera



Hikvision DS-2CD1023G2-LIUF 2 MP Smart Hybrid Light bullet IP kamera yüksək keyfiyyətli 1080p görüntü, 2.8 mm sabit lens və Smart Hybrid Light texnologiyası ilə 30 m məsafəyə qədər gecə rəngli və IR işıq təmin edir. Daxili mikrofon, PoE qidalanma və IP67 hava qoruması sayəsində ev və obyekt mühafizəsi üçün ideal həll.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)<https://eurotechnology.az/product/hikvision/ds-2cd1023g2-liuf>**Texniki göstəricilər****IP**

Növ

**2 MP**

Məqapixel

**LED**

İşıqlandırma

**30 m**

İşıqlandırma məsafəsi

**Sabit**

Obyektiv

**2.8mm**

Fokus

**Mic**

Mikrofon

**IP67**

Qoruma

**Plastik**

Material

**Outdoor**

İş mühiti

## Ətraflı məlumat

| Category               | Specification                                              |
|------------------------|------------------------------------------------------------|
| Image Sensor           | 1/2.9" Progressive Scan CMOS                               |
| Max. Resolution        | 1920 × 1080                                                |
| Min. Illumination      | Color: 0.005 Lux @ (F1.6, AGC ON); B/W: 0 Lux with IR      |
| Shutter Time           | 1/3 s to 1/100,000 s                                       |
| Day & Night            | IR Cut Filter                                              |
| Angle Adjustment       | Pan: 0°–360°; Tilt: 0°–90°; Rotate: 0°–360°                |
| Lens Type              | Fixed focal lens                                           |
| Focal Length Options   | 2.8 mm / 4 mm                                              |
| Aperture               | F1.6                                                       |
| Lens Mount             | M12                                                        |
| FOV (2.8 mm)           | H: 103°; V: 56°; D: 121°                                   |
| FOV (4 mm)             | H: 83°; V: 44°; D: 99°                                     |
| DORI (2.8 mm)          | Detect 45 m / Observe 18 m / Recognize 9 m / Identify 4 m  |
| DORI (4 mm)            | Detect 56 m / Observe 22 m / Recognize 11 m / Identify 5 m |
| Supplement Light Type  | IR + White Light                                           |
| Supplement Light Range | Up to 30 m                                                 |
| Smart Supplement Light | Yes                                                        |
| IR Wavelength          | 850 nm                                                     |
| Main Stream            | 25 fps (50 Hz) / 30 fps (60 Hz) @ 1080p, 720p              |
| Sub Stream             | 25 fps (50 Hz) / 30 fps (60 Hz) @ 640×480, 640×360         |
| Video Compression      | Main: H.265+/H.265/H.264+/H.264; Sub: H.265/H.264/MJPEG    |
| Video Bit Rate         | 32 Kbps – 8 Mbps                                           |
| Bit Rate Control       | CBR / VBR                                                  |
| ROI                    | 1 fixed region (main stream)                               |
| Audio Type             | Mono                                                       |

| Category               | Specification                                                            |
|------------------------|--------------------------------------------------------------------------|
| Built-in Microphone    | Yes                                                                      |
| Audio Compression      | G.711 u/a, G.722.1, G.726, MP2L2, PCM, AAC-LC                            |
| Audio Sampling Rate    | 8 kHz / 16 kHz                                                           |
| Audio Bit Rate         | 16 – 160 Kbps                                                            |
| Network Interface      | 1 × RJ45 10/100 Mbps                                                     |
| Protocols              | TCP/IP, ICMP, DHCP, DNS, HTTP, RTP/RTSP, RTCP, UDP, IPv6, FTP, SMTP, QoS |
| API                    | ONVIF (S/T/G*), ISAPI, SDK                                               |
| Simultaneous Live View | Up to 6 channels                                                         |
| Security               | Password protection, watermark, MAC authentication, security audit log   |
| Client Software        | iVMS-4200, Hik-Connect                                                   |
| Web Browser            | IE 10/11, Chrome 57+, Firefox 52+                                        |
| WDR                    | Digital WDR                                                              |
| SNR                    | ≥ 52 dB                                                                  |
| Image Enhancement      | BLC, HLC, 3D DNR                                                         |
| Privacy Mask           | 4 programmable polygon masks                                             |
| Events                 | Motion detection (human & vehicle), video tampering, exception           |
| Event Linkage          | FTP, email, surveillance center, recording (-F), capture                 |
| On-Board Storage       | microSD/SDHC/SDXC up to 512 GB (-F)                                      |
| Power Supply           | 12 VDC ±25%, max 5 W                                                     |
| PoE                    | IEEE 802.3af, Class 3, max 6.5 W                                         |
| Material               | Metal & Plastic                                                          |
| Dimensions             | 170.8 × 66 × 69.1 mm                                                     |
| Weight                 | Approx. 265 g                                                            |
| Operating Temperature  | -30 °C to 60 °C                                                          |
| Operating Humidity     | ≤ 95% (non-condensing)                                                   |
| Languages              | English, Ukrainian                                                       |
| Protection             | <b>IP67</b>                                                              |

| Category       | Specification                          |
|----------------|----------------------------------------|
| Certifications | FCC, CE-EMC, UL, CB, RoHS, WEEE, REACH |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · [sales@eurotech.az](mailto:sales@eurotech.az)