

## DS-2CD1123G2-I

Hikvision DS-2CD1123G2-I 2 MP dome IP kamera 2.8 mm sabit lenslə geniş baxış bucağı verir, 30 m IR gecə görüşü və EXIR 2.0 infraqırmızı işıqla aydın görüntü təmin edir. IP67 və IK10 qorunma səviyyəsi, PoE/12 VDC qidalanma və effektiv H.265+ video sıxılma ilə villa, ofis və obyektlər üçün etibarlı təhlükəsizlik həllidir.



### Specifications

Model	DS-2CD1123G2-I
Brand	Hikvision
Növ	IP
Meqapixel	2 MP
???qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	2.8mm
???qland?rma	İR
Qoruma	IP67
Material	Metal
?? mühiti	Indoor

## KEY FEATURES

Category	Specification
Image Sensor	1/2.9" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Min. Illumination	Color: 0.01 Lux @ (F2.0, AGC ON); B/W: 0 Lux with IR
Shutter Time	1/3 s – 1/100,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0°–355°; Tilt: 0°–75°
Lens Type	Fixed focal lens
Focal Length Options	2.8 mm / 4 mm
Aperture	F2.0
Lens Mount	M12
FOV (2.8 mm)	H: 104°; V: 58°; D: 123°
FOV (4 mm)	H: 81°; V: 43°; D: 96°
DORI (2.8 mm)	Detect 42 m / Observe 16 m / Recognize 8 m / Identify 4 m
DORI (4 mm)	Detect 57 m / Observe 22 m / Recognize 11 m / Identify 5 m
Supplement Light Type	IR
Supplement Light Range	Up to 30 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Main Stream	25 fps (50 Hz) / 30 fps (60 Hz) @ 1080p, 720p
Sub Stream	25 fps (50 Hz) / 30 fps (60 Hz) @ 640×480, 640×360
Video Compression	Main: H.265+/H.265/H.264+/H.264
Sub-stream Compression	H.265/H.264/MJPEG
Video Bit Rate	32 Kbps – 8 Mbps
Bit Rate Control	CBR / VBR
ROI	1 fixed region (main stream)
WDR	Digital WDR
SNR	≥ 52 dB
Image Enhancement	BLC, HLC, 3D DNR
Image Settings	Rotate, saturation, brightness, contrast, sharpness, gain, white balance
Privacy Mask	4 programmable polygon masks
Ethernet Interface	1 × RJ45 10/100 Mbps
Network Protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP
API	ONVIF (Profile S, T), ISAPI, SDK
Simultaneous Live View	Up to 6 channels
Security	Password protection, watermark, MAC authentication, security audit log
Max Users	Up to 32 users (Admin / Operator / User)
Client Software	iVMS-4200, Hik-Connect
Web Browser	IE 10/11, Chrome 57+, Firefox 52+
Basic Events	Motion detection (human & vehicle), video tampering, exception
Event Linkage	FTP upload, email, surveillance center, capture

---

Category	Specification
Power (DC)	12 VDC $\pm$ 25%, 0.4 A, max 5 W
PoE	IEEE 802.3af, Class 3, max 6.5 W
Material	Metal & Plastic
Camera Dimensions	$\varnothing$ 110.8 $\times$ 84.7 mm
Package Dimensions	134 $\times$ 134 $\times$ 108 mm
Camera Weight	Approx. 520 g
Weight with Package	Approx. 720 g
Operating Temperature	-30 °C to 60 °C
Operating Humidity	$\leq$ 95% (non-condensing)
Languages	English, Ukrainian
General Functions	Heartbeat, anti-flicker, mirror, password reset via email
Protection Rating	IP67, IK10
Certifications	FCC, CE-EMC, UL, CB, RoHS, WEEE, REACH