

HIKVISION

DS-2CD1143G0-I

Kod: 00-00000371 · Kamera



Hikvision DS-2CD1143G0-I 4MP Dome IP Kamera 2.8mm lens ilə geniş baxış sahəsi təmin edir. 30 metr IR gecə görmə funksiyası, kompakt dizayn və yüksək keyfiyyətli görüntü ilə ev və iş yerləri üçün təhlükəsiz və etibarlı həll təklif edir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](https://eurotechnology.az/product/hikvision/ds-2cd1143g0-i)
<https://eurotechnology.az/product/hikvision/ds-2cd1143g0-i>

Texniki göstəricilər



IP

Növ



4 MP

Məqapixel



30 m

İşıqlandırma məsafəsi



İR

İşıqlandırma



Sabit

Obyektiv



2.8mm

Fokus



IP67

Qoruma



Metal

Material



Indoor

İş mühiti

Ətraflı məlumat

Category	Specification
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	2560 × 1440
Min. Illumination	Color: 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR
Shutter Time	1/3 s to 1/100,000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°, Tilt: 0° to 75°
Lens	
Focal Length & FOV	2.8 mm: H 98.0°, V 53.1°, D 114.7° 4 mm: H 78.7°, V 43.1°, D 92.3°
Lens Mount	M12
Focus	Fixed
Aperture	F2.0
Lens Type	Fixed focal lens, 2.8 and 4 mm optional
Iris Type	Fixed
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 30 m
IR Wavelength	850 nm
Smart Supplement Light	Yes
Video	
Main Stream	50 Hz: 20 fps (2560×1440), 25 fps (1920×1080, 1280×720) 60 Hz: 20 fps (2560×1440), 30 fps (1920×1080, 1280×720)
Sub-Stream	50 Hz: 25 fps (640×480, 640×360) 60 Hz: 30 fps (640×480, 640×360)
Video Compression	Main: H.265/H.264/H.264+/H.265+Sub: H.265/H.264/MJPEG

Category	Specification
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline/Main/High Profile
H.265 Type	Main Profile
Region of Interest (ROI)	1 fixed region for main stream
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS
Simultaneous Live View	Up to 6 channels
API	ONVIF, ISAPI
User/Host	Up to 32 users; 3 levels: administrator, operator, user
Client	iVMS-4200, Hik-Connect
Web Browser	Plug-in required: IE 10/11 Plug-in free: Chrome 57+, Firefox 52+, Edge 89+ Local service: Chrome 57+, Firefox 52+, Edge 89+
Image	
Image Settings	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
Day/Night Switch	Auto, Schedule, Day, Night
Wide Dynamic Range (WDR)	120 dB
Image Enhancement	BLC, 3D DNR
Interface	
Ethernet Interface	1 RJ45 10/100 M self-adaptive
Event	
Basic Event	Motion detection, video tampering alarm, exception
Linkage	Upload to FTP, notify surveillance center, send email
General	
Power	12 VDC $\pm$ 25%, 0.58 A, max 7 W, Ø5.5 mm coaxial plug PoE: IEEE 802.3af, Class 3, 36-57 V, 0.24-0.15 A, max 8.5 W

Category	Specification
Material	Base: metal; Cover: plastic
Dimension	Ø111 mm × 82.4 mm (Ø4.4" × 3.2")
Package Dimension	134 × 134 × 108 mm (5.3" × 5.3" × 4.3")
Weight	Approx. 360 g (0.8 lb)
With Package Weight	Approx. 560 g (1.2 lb)
Storage Conditions	-30 °C to 60 °C (-22 °F to 140 °F), Humidity ≤95% (non-condensing)
Startup & Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F), Humidity ≤95% (non-condensing)
Language	English, Ukrainian
General Function	Anti-banding, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter
Approval	
EMC	FCC SDoC, CE-EMC, RCM, IC VoC, KC
Safety	UL, CB, CE-LVD, BIS
Environment	CE-RoHS, WEEE, REACH
Protection	IP67 (IEC 60529-2013), IK10 (IEC 62262:2002)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az