HIKVISION

# DS-2CD1143G0-I

Kod: 00-00000371 · Kamera




Hikvision DS-2CD1143G0-I 4MP Dome IP Kamera 2.8mm lens ilə geniş baxış sahəsi təmin edir. 30 metr IR gecə görmə funksiyası, kompakt dizayn və yüksək keyfiyyətli görüntü ilə ev və iş yerləri üçün təhlükəsiz və etibarlı həll təklif edir.

## Texniki göstəricilər

| | |
|---|---|
| **IP** | Növ |
| **4 MP** | Meqapixel |
| **30 m** | İşıqlandırma məsafəsi |
| **İR** | İşıqlandırma |
| **Sabit** | Obyektiv |
| **2.8mm** | Fokus |
| **IP67** | Qoruma |
| **Metal** | Material |
| **Indoor** | İş mühiti |

## Ətraflı məlumat

| Category | Specification |
|---|---|
| **Camera** | |
| Image Sensor | 1/3" Progressive Scan CMOS |
| Max. Resolution | 2560 × 1440 |
| Min. Illumination | Color: 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR |
| Shutter Time | 1/3 s to 1/100,000 s |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 355°, Tilt: 0° to 75° |
| **Lens** | |
| Focal Length & FOV | 2.8 mm: H 98.0°, V 53.1°, D 114.7°4 mm: H 78.7°, V 43.1°, D 92.3° |
| Lens Mount | M12 |
| Focus | Fixed |
| Aperture | F2.0 |
| Lens Type | Fixed focal lens, 2.8 and 4 mm optional |
| Iris Type | Fixed |
| **Illuminator** | |
| Supplement Light Type | IR |
| Supplement Light Range | Up to 30 m |
| IR Wavelength | 850 nm |
| Smart Supplement Light | Yes |
| **Video** | |
| Main Stream | 50 Hz: 20 fps (2560×1440), 25 fps (1920×1080, 1280×720)60 Hz: 20 fps (2560×1440), 30 fps (1920×1080, 1280×720) |
| Sub-Stream | 50 Hz: 25 fps (640×480, 640×360)60 Hz: 30 fps (640×480, 640×360) |
| Video Compression | Main: H.265/H.264/H.264+/H.265+Sub: H.265/H.264/MJPEG |

| Category | Specification |
|---|---|
| Video Bit Rate | 32 Kbps to 8 Mbps |
| H.264 Type | Baseline/Main/High Profile |
| H.265 Type | Main Profile |
| Region of Interest (ROI) | 1 fixed region for main stream |
| **Network** | |
| Protocols | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS |
| Simultaneous Live View | Up to 6 channels |
| API | ONVIF, ISAPI |
| User/Host | Up to 32 users; 3 levels: administrator, operator, user |
| Client | iVMS-4200, Hik-Connect |
| Web Browser | Plug-in required: IE 10/11Plug-in free: Chrome 57+, Firefox 52+, Edge 89+Local service: Chrome 57+, Firefox 52+, Edge 89+ |
| **Image** | |
| Image Settings | Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser |
| Day/Night Switch | Auto, Schedule, Day, Night |
| Wide Dynamic Range (WDR) | 120 dB |
| Image Enhancement | BLC, 3D DNR |
| **Interface** | |
| Ethernet Interface | 1 RJ45 10/100 M self-adaptive |
| **Event** | |
| Basic Event | Motion detection, video tampering alarm, exception |
| Linkage | Upload to FTP, notify surveillance center, send email |
| **General** | |
| Power | 12 VDC ±25%, 0.58 A, max 7 W, Ø5.5 mm coaxial plugPoE: IEEE 802.3af, Class 3, 36–57 V, 0.24–0.15 A, max 8.5 W |

| Category | Specification |
|---|---|
| Material | Base: metal; Cover: plastic |
| Dimension | Ø111 mm × 82.4 mm (Ø4.4" × 3.2") |
| Package Dimension | 134 × 134 × 108 mm (5.3" × 5.3" × 4.3") |
| Weight | Approx. 360 g (0.8 lb) |
| With Package Weight | Approx. 560 g (1.2 lb) |
| Storage Conditions | -30 °C to 60 °C (-22 °F to 140 °F), Humidity ≤95% (non-condensing) |
| Startup & Operating Conditions | -30 °C to 60 °C (-22 °F to 140 °F), Humidity ≤95% (non-condensing) |
| Language | English, Ukrainian |
| General Function | Anti-banding, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter |
| **Approval** | |
| EMC | FCC SDoC, CE-EMC, RCM, IC VoC, KC |
| Safety | UL, CB, CE-LVD, BIS |
| Environment | CE-RoHS, WEEE, REACH |
| Protection | IP67 (IEC 60529-2013), IK10 (IEC 62262:2002) |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az