

DS-2CD1143G0-I

Hikvision DS-2CD1143G0-I 4MP Dome IP Kamera 2.8mm lens ilə geniş baxış sahəsi təmin edir. 30 metr IR gecə görmə funksiyası, kompakt dizayn və yüksək keyfiyyətli görüntü ilə ev və iş yerləri üçün təhlükəsiz və etibarlı həll təklif edir.



Specifications

Model	DS-2CD1143G0-I
Brand	Hikvision
Növ	IP
Meqapixel	4 MP
???qland?rma m?saf?si	30 m
???qland?rma	İR
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Metal
?? mühiti	Indoor

KEY FEATURES

Category	Specification
Camera	
Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	2560 × 1440
Min. Illumination	Color: 0.01 Lux @(F2.0, AGC ON), B/W: 0 Lux with IR
Shutter Time	1/3 s to 1/100,000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°, Tilt: 0° to 75°
Lens	
Focal Length & FOV	2.8 mm: H 98.0°, V 53.1°, D 114.7°4 mm: H 78.7°, V 43.1°, D 92.3°
Lens Mount	M12
Focus	Fixed
Aperture	F2.0
Lens Type	Fixed focal lens, 2.8 and 4 mm optional
Iris Type	Fixed
Illuminator	
Supplement Light Type	IR
Supplement Light Range	Up to 30 m
IR Wavelength	850 nm
Smart Supplement Light	Yes
Video	
Main Stream	50 Hz: 20 fps (2560×1440), 25 fps (1920×1080, 1280×720)60 Hz: 20 fps (2560×1440), 30 fps (1920×1080, 1280×720)
Sub-Stream	50 Hz: 25 fps (640×480, 640×360)60 Hz: 30 fps (640×480, 640×360)
Video Compression	Main: H.265/H.264/H.264+/H.265+Sub: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline/Main/High Profile
H.265 Type	Main Profile
Region of Interest (ROI)	1 fixed region for main stream
Network	
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6, Bonjour, IPv4, UDP, SSL/TLS
Simultaneous Live View	Up to 6 channels
API	ONVIF, ISAPI
User/Host	Up to 32 users; 3 levels: administrator, operator, user
Client	iVMS-4200, Hik-Connect
Web Browser	Plug-in required: IE 10/11Plug-in free: Chrome 57+, Firefox 52+, Edge 89+Local service: Chrome 57+, Firefox 52+, Edge 89+
Image	
Image Settings	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
Day/Night Switch	Auto, Schedule, Day, Night

Category		Specification
Wide Dynamic Range (WDR)	120 dB	
Image Enhancement	BLC, 3D DNR	
Interface		
Ethernet Interface	1 RJ45 10/100 M self-adaptive	
Event		
Basic Event	Motion detection, video tampering alarm, exception	
Linkage	Upload to FTP, notify surveillance center, send email	
General		
Power	12 VDC ±25%, 0.58 A, max 7 W, Ø5.5 mm coaxial plugPoE: IEEE 802.3af, Class 3, 36–57 V, 0.24–0.15 A, max 8.5 W	
Material	Base: metal; Cover: plastic	
Dimension	Ø111 mm × 82.4 mm (Ø4.4" × 3.2")	
Package Dimension	134 × 134 × 108 mm (5.3" × 5.3" × 4.3")	
Weight	Approx. 360 g (0.8 lb)	
With Package Weight	Approx. 560 g (1.2 lb)	
Storage Conditions	-30 °C to 60 °C (-22 °F to 140 °F), Humidity ≤95% (non-condensing)	
Startup & Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F), Humidity ≤95% (non-condensing)	
Language	English, Ukrainian	
General Function	Anti-banding, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter	
Approval		
EMC	FCC SDoC, CE-EMC, RCM, IC VoC, KC	
Safety	UL, CB, CE-LVD, BIS	
Environment	CE-RoHS, WEEE, REACH	
Protection	IP67 (IEC 60529-2013), IK10 (IEC 62262:2002)	