

DS-2CD1143G2-I

NVR for IP Cameras



Specifications

Model	DS-2CD1143G2-I
Brand	Hikvision
Qoruma	IP67
Növ	IP
Meqapixel	4 MP
??qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	4mm
??qland?rma	IR
Material	Metal
?? mühiti	Indoor

KEY FEATURES

Camera

Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	2560 × 1440
Shutter Time	1/3 s to 1/100,000 s
Min. Illumination	Color: 0.01 Lux @ (F2.0,AGC ON), B/W: 0 Lux with IR
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°, tilt:0° to 75°
Lens	
Lens Type	Fixed focallens, 2.8 and4 mm optional
Focal Length& FOV	2.8 mm, horizontal FOV 99°, vertical FOV 55°, diagonal FOV 116° 4 mm, horizontal FOV 76°, vertical FOV 41°, diagonal FOV 90°
Lens Mount	M12
Iris Type	Fixed
Aperture	F2.0
DORI	
DORI	2.8 mm, D: 59 m, O: 23 m, R: 11 m, I: 5 m 4 mm, D: 79 m, O: 31 m, R: 15 m, I: 7 m
Illuminator	
Supplement LightType	IR
Supplement LightRange	Up to 30 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Video	
	50 Hz:
	20 fps (2560 × 1440)
	25 fps (1920 × 1080, 1280× 720)
Main Stream	60 Hz:
	20 fps (2560 × 1440)
	24 fps (1920 × 1080, 1280× 720)
Sub-Stream	50 Hz: 25 fps (1280 × 720, 640× 480, 640 ×360)
	60 Hz: 24 fps (1280 × 720, 640× 480, 640 ×360)
Video Compression	Main stream:H.265+/H.265/H.264+/H.264 Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps to 8 Mbps

H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR/VBR
Region of Interest (ROI)	1 fixed regionfor main stream
Network	
	Password protection, complicated password, watermark,
Security	IP address filter,basic and digest authentication for HTTP, WSSEand digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Simultaneous LiveView	Up to 6 channels
API	Open Network VideoInterface (Profile S, Profile T), ISAPI, SDK
Protocols	TCP/IP, ICMP, DHCP,DNS, HTTP, RTP,RTSP, NTP, IGMP,IPv6, UDP, QoS,FTP, SMTP
User/Host	Up to 32 users 3 levels: administrator, operator, and user
Client	iVMS-4200, Hik-Connect
Web Browser	Plug-in required liveview: IE 10,IE 11 Local service: Chrome 57.0+, Firefox 52.0+
Image	
Wide Dynamic Range (WDR)	120 dB
SNR	≥ 52 dB
Day/Night Switch	Day, Night, Auto,Schedule
Image Enhancement	BLC, HLC, 3D DNR
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser
Privacy Mask	4 programmable polygonprivacy masks
Interface	
Ethernet Interface	1 RJ45 10 M/100M self-adaptive Ethernet port
Event	
Basic Event	Motion detection (support alarm triggering by specified targettypes (human and vehicle)), videotampering alarm, exception
Linkage	Upload to FTP, sendemail, notify surveillance center, trigger capture
General	
Power	12 VDC± 25%, 0.4 A, max.5 W, Ø5.5 mm coaxialpower plug