

# DS-2CD1321G0E-I

DS-2CD1321G0E-I, 4mm 2mp IR 30m Turret IP Kamera



Model	DS-2CD1321G0E-I
Brend	Hikvision
Növ	IP
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	4
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik

## Specification

Camera	
Image Sensor	1/2.8" progressive scan CMOS
Min. Illumination	Color: 0.01Lux @(F1.2, AGC ON), 0Lux with IR
Shutter Speed	1/3s to 1/100,000 s, support slowshutter
Lens	2.8 mm @F2.0, horizontal field of view 95°, 4 mm @F2.0, horizontal field of view 83.6° 6 mm @F2.0, horizontal field of view 55°
Lens Mount	M12
Day & Night	IR cut filter with auto switch
3-Axis Adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotation: 0° to 360°
DNR(Digital Noise Reduction)	3D DNR
WDR (WideDynamic Range)	Digital WDR
Compression Standard	
Video Compression	Main stream: H.264+/H.264 Sub stream: H.264/MJPEG
H.264 Type	Baseline Profile/Main Profile
Video BitRate	32 Kbpsto8 Mbps
Image	
Max. Resolution	1920 × 1080
Main Stream Max. FrameRate	50Hz: 25fps @(1920× 1080, 1280× 960, 1280 × 720) 60Hz: 30fps@(1920 × 1080,1280 × 960, 1280× 720)
Sub-stream Max. Frame Rate	50Hz: 25fps@(704 × 576,640 × 480, 352 × 288,320 × 240) 60Hz: 30fps@(704 × 480, 640 × 480, 352 × 240,320 × 240)

Image Settings	Brightness, saturation, contrast, sharpness are adjustable via web browser or client software
Day/Night Switch	Support auto, scheduled
Others	Mirror, BLC (area configurable), region of interest (support 1 fixed region)
<i>Network</i>	
Network Storage	NAS (NFS,SMB/CIFS)
Detections	Motion Detection
Alarms	Video tampering, network disconnected, IP address conflicted
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, Bonjour
Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
General Function	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark, IP address filter
<i>Interface</i>	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
<i>General</i>	
Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)
Power Supply	12VDC ± 25%, PoE (802.3af)
Power Consumption	Max. 4 W / 6 W (PoE)
Ingress Protection	IP67
IR Range	Up to 30 m
Dimensions	Φ 85.5 mm × 70 mm (3.38" × 2.76")
Weight	350 g (0.77 lb.)