

DS-2CD1321G0E-I

DS-2CD1321G0E-I, 4mm 2mp IR 30m Turret IP Kamera Hikvision



Specifications

Model	DS-2CD1321G0E-I
Brand	Hikvision
Qoruma	IP67
Növ	IP
Meqapixel	2 MP
??qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	4mm
??qland?rma	IR
Material	Plastik
?? mühiti	Indoor

KEY FEATURES

Camera

Image Sensor	1/2.8" progressive scan CMOS
Min. Illumination	Color: 0.01Lux @(F1.2, AGC ON), 0Lux with IR
Shutter Speed	1/3s to 1/100,000 s, support slowshutter
Lens	2.8 mm @F2.0, horizontal field of view 95°, 4 mm @F2.0, horizontal field of view 83.6° 6 mm @F2.0, horizontal field of view 55°
Lens Mount	M12
Day & Night	IR cut filter with auto switch
3-Axis Adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotation: 0° to 360°

DNR (Digital Noise Reduction) 3D DNR

WDR (Wide Dynamic Range) Digital WDR

Compression Standard

Video Compression Main stream: H.264+/H.264 Sub stream: H.264/MJPEG

H.264 Type Baseline Profile/Main Profile

Video BitRate 32 Kbps to 8 Mbps

Image

Max. Resolution 1920 × 1080

Main Stream

Max. FrameRate 50Hz: 25fps @(1920 × 1080, 1280 × 960, 1280 × 720)

60Hz: 30fps @(1920 × 1080, 1280 × 960, 1280 × 720)

Sub-stream Max. Frame Rate

50Hz: 25fps @(704 × 576, 640 × 480, 352 × 288, 320 × 240)

60Hz: 30fps @(704 × 480, 640 × 480, 352 × 240, 320 × 240)

Image Settings

Brightness, saturation, contrast, sharpness are adjustable via web browser or client software

Day/Night Switch

Support auto, scheduled

Others

Mirror, BLC (area configurable), region of interest (support 1 fixed region)

Network

Network Storage NAS (NFS, SMB/CIFS)

Detections Motion Detection

Alarms

Video tampering, network disconnected, IP address conflicted

Protocols

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS,

RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP,

802.1X, QoS, IPv6, Bonjour

Standard

ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI

General Function	Anti-flicker,heartbeat, mirror, password protection, privacy mask,watermark, IP address filter
<i>Interface</i>	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
<i>General</i>	
Operating Conditions	-30 °C to60 °C (-22 °F to140 °F), humidity: 95% or less(non-condensing)
Power Supply	12VDC± 25%, PoE(802.3af)
Power Consumption	Max. 4 W/6 W (PoE)
Ingress Protection	IP67
IR Range	Up to 30 m
Dimensions	Φ 85.5 mm × 70 mm(3.38"× 2.76")
Weight	350 g (0.77 lb.)