

# DS-2CD1321G0E-I-ECO

DS-2CD1321G0E-I ECO 2.8mm C 2 MP Fixed Turret N



Model	DS-2CD1321G0E-I-ECO
Brend	Hikvision
Növ	IP
Meqapixel	2 MP
İşıqlandırma məsafəsi	30 m
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
Qoruma	IP67
Material	Plastik

## Specification

Image Sensor	1/2.8" progressive scan CMOS
Min. Illumination	Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @ (F2.0, AGC ON)
Shutter Speed	1/3 s to 1/100, 000 s
Slow Shutter	Yes
Auto-Iris	No
Day &Night	IR cut filter
Digital Noise Reduction	3D DNR
WDR	DWDR
Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotation: 0° to 360°
Lens	
Focal Length	2.8 mm
Aperture	F2.0
Focus	Fixed
FOV	horizontal FOV 114°, vertical FOV 62°, diagonal FOV 135°
Lens Mount	M12
IR	
IR Range	Up to 30 m
Wavelength	850 nm

<b>Compression Standard</b>	
<b>Video Compression</b>	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG
<b>H.264 Type</b>	Main Profile/High Profile/Baseline Profile
<b>H.265 Type</b>	Main Profile
<b>Video Bit Rate</b>	32 Kbps to 8 Mbps
<b>Smart Feature-set</b>	
<b>Region of Interest</b>	1 fixed region for main stream
<b>Image</b>	
<b>Max. Resolution</b>	1920 × 1080
<b>Main Stream</b>	50Hz: 25fps (1920 × 1080, 1280 × 960, 1280 × 720)
<b>Max. Frame Rate</b>	60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)
<b>Sub-stream</b>	50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)
<b>Max. Frame Rate</b>	60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)
<b>Image Enhancement</b>	BLC, 3D DNR
<b>Image Settings</b>	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
<b>Day/Night Switch</b>	Auto, scheduled, day, night
<b>Network</b>	
<b>Alarm Trigger</b>	Motion detection, video tampering alarm, illegal login
<b>Protocols</b>	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
<b>General Function</b>	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
<b>Firmware Version</b>	V5.5.70
<b>API</b>	ONVIF (PROFILE S), ISAPI
<b>Simultaneous Live View</b>	Up to 6 channels
<b>User/Host</b>	Up to 32 users 3 levels: Administrator, Operator and User
<b>General</b>	
<b>Operating Conditions</b>	-30 °C to 60 °C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)
<b>Power Supply</b>	12 VDC ± 25%, 5.5 mm coaxial power plug PoE (802.3af, class 3)
<b>Power Consumption and Current</b>	12 VDC, 0.3 A, max: 3.5 W PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, Max: 4.5 W
<b>Ingress Protection</b>	IP67
<b>Material</b>	Camera body: metal, bottom base : plastic