

DS-2CD1323G0E-I

NVR for IP Cameras



Specifications

Model	DS-2CD1323G0E-I
Brand	Hikvision
Qoruma	IP67
Növ	IP
Meqapixel	2 MP
??qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	2.8mm
??qland?rma	IR
?? mühiti	Indoor

KEY FEATURES

Camera

Image Sensor	1/2.8" progressive scan CMOS
Min. Illumination	Color: 0.01 Lux @(F1.2, AGC ON), 0.028Lux @ (F2.0,AGC ON)
Shutter Speed	1/3 s to 1/100, 000 s
Slow Shutter	Yes
Auto-Iris	No
Day &Night	IR cut filter
Digital Noise Reduction	3D DNR
WDR	DWDR
Angle Adjustment	Pan: 0° to 360°,tilt: 0° to 75°,rotation: 0° to 360°

Lens

Focal Length	2.8 mm, 4 mm
Aperture	F2.0
Focus	Fixed
FOV	2.8 mm, horizontal FOV 114.8°,vertical FOV 62°,diagonal FOV 135.5° 4 mm, horizontal FOV 86°, vertical FOV 46.5°, diagonal FOV 102.5°

Lens Mount	M12
-------------------	-----

IR

IR Range	Up to 30 m
Wavelength	850 nm

Compression Standard

Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub stream: H.265/H.264/MJPEG
H.264 Type	Main Profile/High Profile/Baseline Profile
H.265 Type	Main Profile
Video Bit Rate	32 Kbps to 8 Mbps

Smart Feature-set

Region of Interest	1 fixed regionfor main stream
---------------------------	-------------------------------

Image

Max. Resolution	1920 × 1080
Main Stream Max. FrameRate	50Hz: 25fps(1920 × 1080, 1280× 960, 1280× 720) 60Hz: 30fps(1920 × 1080, 1280× 960, 1280× 720)

Sub-stream Max. Frame Rate	50Hz: 25fps (640× 480, 640× 360, 320× 240) 60Hz: 30fps(640 × 480,640 × 360,320 × 240)
-----------------------------------	--

Image Enhancement	BLC, 3D DNR
Image Settings	Saturation, brightness, contrast, sharpness, AGC, white balance adjustable by client software or web browser
Day/Night Switch	Auto, scheduled, day, night

Network

Alarm Trigger	Motion detection, videotampering alarm, illegal login
----------------------	---

Protocols	TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, RTP, RTSP, RTCP, NTP, IGMP, QoS, UDP
General Function	Anti-flicker, heartbeat, mirror, password protection, privacy mask, watermark
Firmware Version	V5.5.83
API	ONVIF (PROFILE S), ISAPI
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Client	iVMS-4200, Hik-Connect, iVMS-5200, iVMS-4500
Web Browser	IE8+, Chrome31.0-44, Firefox 30.0-51, Safari 8.0+
Interface	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
General	
Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F), humidity: 95% or less (non-condensing)
Power Supply	12 VDC ± 25%, 5.5 mm coaxial power plug PoE (802.3af, class 3)
Power Consumption and Current	12 VDC, 0.3A, max: 3.5 W PoE: (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, Max: 4.5 W
Ingress Protection	IP67
Material	Camera body: metal, bottom base : plastic
Dimensions	Camera: Ø 110 mm × 93.2 mm (4.3" × 3.7") With package: 150 mm × 150 mm × 141 mm (5.9" × 5.9" × 5.6")
Weight	Camera: approx. 360 g (0.8lb.) With package: approx. 610 g (1.3 lb.)