

DS-2CD1343G2-IUF



Model	DS-2CD1343G2-IUF
Brend	Hikvision
Növ	IP
Meqapixel	4 MP
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8
İşıqlandırma	İR
İşıqlandırma məsafəsi	30 m
Qoruma	IP67
Material	Metal

Specification

Camera	
Image Sensor	1/3" Progressive Scan CMOS
Max. Resolution	2560 × 1440
Shutter Time	1/3 s to 1/100,000 s
Min. Illumination	Color: 0.01 Lux @ (F2.0, AGC ON), B/W: 0 Lux with IR
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°
Lens	
Lens Type	Fixed focallens, 2.8 and 4 mm optional
Focal Length& FOV	2.8 mm, horizontal FOV 99°, vertical FOV 55°, diagonal FOV 116° 4 mm, horizontal FOV 76°, vertical FOV 41°, diagonal FOV 90°
Lens Mount	M12
Iris Type	Fixed
Aperture	F2.0
DORI	
DORI	2.8 mm,D: 59 m, O: 23 m, R: 11 m, I: 5 m 4 mm, D: 79 m, O: 31 m, R: 15 m, I: 7 m
Illuminator	
Supplement LightType	İR
Supplement LightRange	Up to 30 m
Smart Supplement Light	Yes
İR Wavelength	850 nm

Video	
Main Stream	<p>50 Hz:</p> <p>20 fps (2560× 1440)</p> <p>25 fps (1920× 1080, 1280 ×720)</p> <p>60 Hz:</p> <p>20 fps (2560× 1440)</p> <p>24 fps (1920× 1080, 1280 ×720)</p>
Sub-Stream	<p>50 Hz: 25 fps(1280 × 720, 640 × 480,640 × 360)</p> <p>60 Hz: 24 fps (1280 × 720, 640 × 480, 640 × 360)</p>
Video Compression	<p>Main stream: H.265+/H.265/H.264+/H.264</p> <p>Sub-stream: H.265/H.264/MJPEG</p>
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR/VBR
Region of Interest (ROI)	1 fixed regionfor main stream
Audio	
Audio Type	-U: Mono sound
Environment NoiseFiltering	-U: Yes
Audio Sampling Rate	-U: 8 kHz/16 kHz
Audio Compression	-U: G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC-LC
Audio Bit Rate	-U: 64 Kbps (G.711 ulaw)/64 Kbps (G.711 alaw)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 160 Kbps (MP2L2)/16 to 64 Kbps (AAC-LC)

Network	
Security	<p>Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSEand digest authentication for Open NetworkVideo Interface, security auditlog, host authentication (MAC address)</p>
Simultaneous Live View	Up to 6 channels
API	<p>Open Network VideoInterface (Profile S, Profile T, Profile G (only -F model supports)), ISAPI, SDK</p>
Protocols	TCP/IP, ICMP, DHCP,DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP
User/Host	<p>Up to 32 users</p> <p>3 levels: administrator, operator, and user</p>
Client	iVMS-4200, Hik-Connect
Web Browser	<p>Plug-in required live view: IE 10, IE 11</p> <p>Local service: Chrome 57.0+, Firefox52.0+</p>
Image	
Wide Dynamic Range (WDR)	120 dB

SNR	≥ 52 dB
Day/Night Switch	Day, Night, Auto, Schedule
Image Enhancement	BLC, HLC, 3D DNR
Image Settings	Rotate mode, saturation, brightness, contrast, sharpness, gain, white balance, adjustable by client software or web browser
Privacy Mask	4 programmable polygon privacymasks
Interface	
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
On-Board Storage	-F: Built-in memorycard slot, support microSD/microSDHC/microSDXCcard, up to 256 GB
Built-in Microphone	-U: Yes
Reset Key	-F: Yes
Event	
Basic Event	Motion detection (support alarm triggering by specified targettypes (human and vehicle)), videotampering alarm, exception
Linkage	Upload to FTP/memory card(-F), send email, notify surveillance center, trigger recording (-F), trigger capture
General	
Power	12 VDC ± 25%, 0.4 A, max. 5 W, Ø5.5mm coaxial powerplug PoE: 802.3af, Class 3, 36 V to 57 V, 0.2 A to 0.15 A, max. 6.5 W
Material	Metal & Plastic
Dimension	Ø110 mm × 85.3mm (Ø4.3" × 3.4")
Package Dimension	150 mm × 150 mm × 141 mm (5.9" × 5.9" × 5.6")
Weight	-I: Approx. 330 g (0.7lb.); -IUF: Approx. 340 g (0.7lb.)
With Package Weight	-I: Approx. 550 g (1.2 lb.); -IUF: Approx. 560 g (1.2lb.)
Storage Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Startup and Operating Conditions	-30 °C to 60 °C (-22 °F to 140 °F). Humidity 95% or less (non-condensing)
Language	English, Ukrainian
General Function	Heartbeat, anti-banding, mirror, password protection, password reset via email

Approval

EMC	FCC: 47 CFR Part 15, Subpart B CE-EMC: EN 55032: 2015, EN 61000-3-2:2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4: 2011 +A1: 2014 RCM: AS/NZS CISPR 32: 2015 IC: ICES-003: Issue 7 KC: KN32: 2015, KN35:2015
Safety	UL: UL 62368-1 CB: IEC 62368-1: 2014+A11 CE-LVD: EN 62368-1: 2014/A11: 2017 BIS: IS 13252 (Part 1): 2010/IEC 60950-1: 2005
Environment	CE-RoHS: 2011/65/EU WEEE: 2012/19/EU Reach: Regulation (EC) No 1907/2006
Protection	IP67: IEC 60529-2013