eurotech
Taste of technology

TEXNIKI SƏNƏD

11.11.2026

HIKVISION

DS-2CD1T23G2-LIUF

Kod: 00-00005650 · Kamera



Hikvision DS-2CD1T23G2-LIUF 2 MP 1080p kamera 4 mm sabit lens və Smart Hybrid Light — IR + LED işıqlandırma ilə gecə-gündüz aydın görüntü təmin edir. 50 m IR məsafəsi, 512 GB-a qədər microSD yaddaş dəstəyi, daxili mikrofon, PoE / 12 VDC qidalanma və IP67 su/toz müqaviməti ilə ev və obyektlər üçün etibarlı təhlükəsizlik həllidir.

Texniki göstəricilər

IP Növ	**2 MP** Meqapixel
LED İşıqlandırma	**50 m** İşıqlandırma məsafəsi
Mic Mikrofon	**Sabit** Obyektiv
4mm Fokus	**IP67** Qoruma
Plastik Material	**MicroSD** Yaddaş

Outdoor
İş mühiti

Ətraflı məlumat

Category	Specification
Image Sensor	1/2.9" Progressive Scan CMOS
Max. Resolution	1920 × 1080
Min. Illumination	Color: 0.005 Lux @ (F1.6, AGC ON); B/W: 0 Lux with IR
Shutter Time	1/3 s to 1/100,000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0°–360°, Tilt: 0°–180°, Rotate: 0°–360°
Specification	**Details**
Lens Type	Fixed focal lens, 4 mm or 6 mm
Focal Length & FOV	**4 mm:** 83°(H) / 44°(V) / 99°(D) **6 mm:** 51°(H) / 27°(V) / 60°(D)
Lens Mount	M12
Aperture	F1.6
Specification	**Details**
Light Type	IR + White Light
Range	Up to 50 m
Smart Light	Yes
IR Wavelength	850 nm
Specification	**Details**
Main Stream	25/30 fps @ 1080p / 720p
Sub Stream	25/30 fps @ 640×480 / 640×360
Compression	H.265+/H.265/H.264+/H.264, MJPEG
Bitrate	32 Kbps – 8 Mbps
ROI	1 fixed region
Specification	**Details**
Audio Type	Mono, built-in mic

Category	Specification
Noise Filtering	Yes
Sampling Rate	8 kHz / 16 kHz
Compression	G.711, G.722.1, G.726, MP2L2, PCM, AAC-LC
Specification	**Details**
Protocols	TCP/IP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, FTP, SMTP
Security	Password protection, watermark, audit log, MAC auth
Live View	Up to 6 users
Users	32 users (Admin / Operator / User)
API	ONVIF S/T/G (G only for -F), ISAPI, SDK
Specification	**Details**
WDR	Digital WDR
SNR	≥ 52 dB
Enhancements	BLC, HLC, 3D DNR
Settings	Brightness, contrast, saturation, gain, sharpness, WB, rotate
Privacy Mask	4 polygon masks
Specification	**Details**
Ethernet	1 × RJ45 10/100M
Storage (-F model)	microSD up to 512 GB
Reset	Yes (-F)
Specification	**Details**
Basic Events	Motion (human/vehicle), tampering, exception
Linkage	FTP/upload, email, center notify, recording (-F), capture
Specification	**Details**
Power	12V DC (6W max) / PoE (7W max)
Material	Metal + Plastic
Dimension	83.7 × 80.7 × 205.6 mm
Weight	580 g

Category	Specification
Protection	IP67
Operating Temp	-30 °C to 60 °C
Approvals	FCC, CE, UL, RoHS, etc.

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az