

HIKVISION

DS-2CD2023G0-I

Kod: 00-00002750 · Kamera



Hikvision DS-2CD2023G0-I 2MP Network Kamera 2.8mm lens ilə geniş baxış sahəsi təmin edir. IR gecə görmə funksiyası ilə zəif işıqda belə dəqiq görüntü əldə edilir. Ev və iş yerləri üçün etibarlı, yüksək keyfiyyətli təhlükəsizlik həllidir.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](https://eurotechnology.az/product/hikvision/ds-2cd2023g0-i)
<https://eurotechnology.az/product/hikvision/ds-2cd2023g0-i>

Texniki göstəricilər

	IP Növ		2 MP Məqapixel
	30 m İşıqlandırma məsafəsi		IR İşıqlandırma
	Sabit Obyektiv		2.8mm Fokus
	IP67 Qoruma		Plastik Material
	MicroSD Yaddaş		Outdoor İş mühiti

Ətraflı məlumat

Category	Specification
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Wide Dynamic Range	120 dB
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
Lens	
Focus	Fixed
Lens Type	2.8 / 4 / 6 / 8 mm
FOV	2.8 mm: H 103°, V 59°, D 118° 4 mm: H 86°, V 46°, D 102° 6 mm: H 54°, V 30°, D 62° 8 mm: H 43°, V 23°, D 50°
Aperture	F2.0
Lens Mount	M12
Aperture Type	Fixed
Illuminator	
IR Range	Up to 30 m
Wavelength	850 nm
Video	
Max. Resolution	1920 × 1080
Main Stream	50Hz: 25 fps (1920×1080, 1280×960, 1280×720) 60Hz: 30 fps (1920×1080, 1280×960, 1280×720)
Sub Stream	50Hz: 25 fps (640×480, 640×360, 320×240) 60Hz: 30 fps (640×480, 640×360, 320×240)
Third Stream	50Hz: 25 fps (1920×1080, 1280×720, 640×360, 352×288) 60Hz: 30 fps (1920×1080, 1280×720, 640×360, 352×240)

Category	Specification
Video Compression	Main: H.265/H.264Sub: H.265/H.264/MJPEGThird: H.265/H.264
Video Bit Rate	32 Kbps to 16 Mbps
H.264 Type	Main Profile / High Profile
H.265 Type	Main Profile
H.264+ / H.265+	Main stream supports
Scalable Video Coding (SVC)	H.264 and H.265 encoding
Network	
Simultaneous Live View	Up to 6 channels
API	ONVIF (Profile S/G/T), ISAPI, SDK, Ehome
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS, WebSocket
User/Host	Up to 32 users; 3 levels: Administrator, Operator, User
Security	Password protection, HTTPS encryption, 802.1X authentication, watermark, IP filter, basic/digest HTTP/HTTPS auth, WSSE & digest ONVIF auth, TLS1.2
Network Storage	Micro SD/SDHC/SDXC (up to 128 GB), local storage, NAS (NFS, SMB/CIFS), ANR
Client	iVMS-4200, Hik-Connect, Hik-Central
Web Browser	Plug-in required: IE8+Plug-in free: Chrome 57+, Firefox 52+, Safari 11+Local Service: Chrome 41+, Firefox 30+
Alarm Trigger	Motion detection, video tampering, network disconnected, IP conflict, illegal login, HDD full/error
Image	Day/Night Switch: Day/Night/Auto/Schedule DNR: 3D DNR Image Enhancement: BLC / 3D DNR / HLCImage Settings: Rotate, saturation, brightness, contrast, sharpness, AGC, white balance

Category	Specification
Interface	Video Output: None On-board Storage: Micro SD/SDHC/SDXC up to 128 GB Hardware Reset: Yes Communication: 1 RJ45 10/100M self-adaptive
Event	Basic: Motion, tampering, exception Smart: Line crossing, intrusion, face detection Face Detection: Yes
General	Linkage: Trigger recording/upload/notification via memory card, FTP, HTTP, NAS, Email Firmware Version: 5.6.3 Web Client Language: 32 languages
General Function	One-key reset, anti-flicker, three streams, heartbeat, mirror, password protection, privacy mask, watermark, IP filter
Startup & Operating Conditions	-30 °C to 60 °C (-22 °F to +140 °F), Humidity ≤95% (non-condensing)
Power Supply	12 VDC ± 25%, Φ 5.5 mm coaxial plug, PoE (802.3af, class 3)
Power Consumption & Current	12 VDC: 0.5 A, max 6 W PoE: 0.2-0.1 A, max 7.5 W
Camera Dimension	Camera: Φ70 × 155.03 mm (Φ2.8" × 6.1")Package: 216 × 121 × 118 mm (8.5" × 4.8" × 4.7")
Camera Weight	Camera: Approx. 420 g (0.9 lb)With Package: Approx. 700 g (1.5 lb)
Approval	
Protection	IP67

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az