eurotech
Taste of technology

TEXNIKI SƏNƏD

11.11.2026

HIKVISION

DS-2CD2047G2-L

Kod: 00-00003016 · Kamera



Hikvision DS-2CD2047G2-L 4MP Bullet IP Kamera 2.8mm lens, 40m ColorVu LED və AcuSense texnologiyası ilə dəqiq insan və avtomobil aşkarlanmasını təmin edir. Gündüz və gecə yüksək keyfiyyətli görüntü üçün ideal təhlükəsizlik həllidir.

Texniki göstəricilər

IP Növ	**4 MP** Meqapixel
LED İşıqlandırma	**40 m** İşıqlandırma məsafəsi
Sabit Obyektiv	**2.8mm** Fokus
Mic Mikrofon	**IP67** Qoruma
Plastik Material	**MicroSD** Yaddaş

Outdoor
İş mühiti

Ətraflı məlumat

Category	Specification
Camera	
Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	2688 × 1520
Min. Illumination	Color: 0.0005 Lux @(F1.0, AGC ON), 0 Lux with white light
Shutter Time	1/3 s to 1/100,000 s
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°
Lens	
Lens Type	Fixed focal lens, 2.8, 4, and 6 mm optional
Focal Length & FOV	2.8 mm: H 112°, V 61°, D 134°4 mm: H 95°, V 51°, D 115°6 mm: H 58°, V 31°, D 69°
Lens Mount	M16
Iris Type	Fixed
Aperture	F1.0
Depth of Field	2.8 mm: 2.5 m to ∞4 mm: 3.5 m to ∞6 mm: 7.5 m to ∞
DORI	2.8 mm: D 58 m, O 23 m, R 11 m, I 6 m4 mm: D 77 m, O 30 m, R 15 m, I 7 m6 mm: D 115 m, O 45 m, R 23 m, I 11 m
Illuminator	
Supplement Light Type	White Light
Supplement Light Range	40 m
Smart Supplement Light	Yes
Video	
Main Stream	50 Hz: 25 fps (2688×1520, 1920×1080, 1280×720)60 Hz: 30 fps (2688×1520, 1920×1080, 1280×720)
Sub Stream	50 Hz: 25 fps (1280×720, 640×480, 640×360)60 Hz: 30 fps (1280×720, 640×480, 640×360)

Category	Specification
Third Stream	50 Hz: 10 fps (1920×1080, 1280×720, 640×480, 640×360)60 Hz: 10 fps (1920×1080, 1280×720, 640×480, 640×360)*Supported under certain settings*
Video Compression	Main: H.265/H.264/H.265+/H.264+Sub: H.265/H.264/MJPEGThird: H.265/H.264
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline / Main / High Profile
H.265 Type	Main Profile
Bit Rate Control	CBR / VBR
Scalable Video Coding (SVC)	H.264 and H.265 encoding
ROI	1 fixed region for main stream and sub-stream
Audio	
Audio Compression	G.711ulaw / G.711alaw / G.722.1 / G.726 / MP2L2 / PCM / MP3 / AAC-LC
Audio Bit Rate	8–320 Kbps depending on codec
Audio Sampling Rate	8 kHz / 16 kHz / 32 kHz / 44.1 kHz / 48 kHz
Environment Noise Filtering	Yes
Network	
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4/IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, ARP, WebSocket, WebSockets
Simultaneous Live View	Up to 6 channels
API	ONVIF (Profile S/G/T), ISAPI, SDK
User/Host	Up to 32 users; 3 levels: administrator, operator, user
Security	Password protection, HTTPS encryption, IP filter, Security Audit Log, HTTP/HTTPS digest, TLS1.1/1.2, WSSE for ONVIF
Network Storage	MicroSD/SDHC/SDXC (up to 512 GB), NAS (NFS, SMB/CIFS), ANR, card encryption & health detection
Client	iVMS-4200, Hik-Connect, Hik-Central

Category	Specification
Web Browser	IE 10/11 (plug-in), Chrome 57+, Firefox 52+, Edge 89+ (plug-in free)
Image	
Image Parameters Switch	Yes
Image Settings	Rotate, saturation, brightness, contrast, sharpness, gain, white balance
Day/Night Switch	Auto / Schedule
WDR	130 dB
SNR	≥ 52 dB
Image Enhancement	BLC / HLC / 3D DNR
Interface	
Ethernet Interface	1 RJ45 10/100M self-adaptive
On-Board Storage	MicroSD/SDHC/SDXC up to 512 GB
Built-in Microphone	Yes
Reset Key	Yes
Event	Basic: Motion (human/vehicle), video tampering, exceptionSmart: Line crossing, intrusion, region entrance/exiting, scene change detection
Linkage	Upload to NAS/memory card/FTP, notify center, trigger recording/capture, send email
Deep Learning Function	Face Capture
General	
Power Supply	12 VDC ± 25%, 0.5 A, max 6 W, Ø5.5 mm coaxial plug; PoE 802.3af Class 3, 36–57 V, 0.25–0.15 A, max 7.5 W
Dimension	215.2 × 78.8 × 78.6 mm (8.5" × 3.1" × 3.1")
Package Dimension	315 × 137 × 141 mm (12.4" × 5.4" × 5.6")
Weight	Camera: 695 g (1.5 lb), With package: 1090 g (2.4 lb)
Storage Conditions	-30 °C to 60 °C, humidity ≤ 95% (non-condensing)
Startup & Operating Conditions	-30 °C to 60 °C, humidity ≤ 95% (non-condensing)

Category	Specification
Language	33 languages (English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese-Brazil, Ukrainian)
General Function	Anti-flicker, heartbeat, mirror, privacy mask, flash log, password reset via email, pixel counter
Approval	
EMC	FCC SDoC (47 CFR Part 15, Subpart B); CE-EMC; RCM; IC VoC; KC
Safety	UL, CB, CE-LVD, LOA
Environment	CE-RoHS; WEEE; Reach
Protection	IP67 (IEC 60529-2013)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az