HIKVISION

DS-2CD2067G2H-LI EF

Kod: 00-00005208 · Kamera



Hikvision DS-2CD2067G2H-LI EF 6 MP mini bullet IP kamera ColorVu texnologiyası ilə gecə vaxtı belə rəngli və detallı görüntü təqdim edir. Smart Hybrid Light sayəsində IR və ağ işıq avtomatik uyğunlaşır. 2.8 mm geniş bucaqlı lens, daxili mikrofon, PoE dəstəyi və IP67 qorunma səviyyəsi ilə açıq məkanlar üçün ideal təhlükəsizlik həllidir.

Texniki göstəricilər

IP Növ	**5 MP** Meqapixel
LED İşıqlandırma	**40 m** İşıqlandırma məsafəsi
Mic Mikrofon	**Sabit** Obyektiv
2.8mm Fokus	**IP67** Qoruma
Metal Material	**MicroSD** Yaddaş

Outdoor
İş mühiti

Ətraflı məlumat

Category	Specification
Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	**3200 × 1800 (5MP+)**
Min. Illumination	Color: 0.0005 Lux @ (F1.0, AGC ON); 0 Lux with light
Shutter Time	1/3 s – 1/100,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0°–360°; Tilt: 0°–90°; Rotate: 0°–360°
Lens Type	Fixed focal lens
Focal Length Options	2.8 mm / 4 mm
Lens Mount	M16
Aperture	**F1.0**
Depth of Field (2.8 mm)	3.3 m – ∞
Depth of Field (4 mm)	3.8 m – ∞
FOV (2.8 mm)	H: 105.1°; V: 54.8°; D: 128.2°
FOV (4 mm)	H: 90.0°; V: 45.8°; D: 109.4°
DORI (2.8 mm)	Detect 89 m / Observe 35 m / Recognize 17 m / Identify 8 m
DORI (4 mm)	Detect 109 m / Observe 43 m / Recognize 21 m / Identify 10 m
Supplement Light Type	IR + White Light
Supplement Light Range	Up to **40 m**
Smart Supplement Light	Yes
IR Wavelength	850 nm
Main Stream (50 Hz)	25 fps @ 3200×1800, 2688×1520, 1080p, 720p
Main Stream (60 Hz)	24 fps @ 3200×1800; 30 fps @ others
Sub-Stream	25/30 fps @ 720p, VGA, 640×360
Third Stream	10 fps @ 1080p, 720p, VGA, 640×360*
Video Compression	H.265/H.264/H.265+/H.264+

Category	Specification
Video Bit Rate	**32 Kbps – 16 Mbps**
SVC	H.264 & H.265
Bit Rate Control	CBR / VBR
ROI	1 fixed region (main & sub-stream)
Audio Compression	G.711, G.722.1, G.726, MP2L2, PCM, MP3, AAC-LC
Audio Sampling Rate	8 / 16 / 32 / 44.1 / 48 kHz
Environment Noise Filtering	Yes
Ethernet Interface	1 × RJ45 10/100 Mbps
Network Protocols	TCP/IP, HTTP(S), FTP, DHCP, DNS, RTSP, RTP, IPv4/IPv6, SNMP, QoS, SSL/TLS, WebSocket, SFTP
API	ONVIF (Profile S/G/T), ISAPI, SDK, ISUP
Simultaneous Live View	Up to 6 channels
Max Users	Up to 32 users (Admin / Operator / User)
Security	HTTPS, 802.1X, IP filter, TLS 1.1/1.2/1.3, watermark, audit log
Network Storage	NAS (NFS, SMB/CIFS), ANR
Client Software	iVMS-4200, Hik-Connect, Hik-Central
Web Browser	IE 10/11, Chrome 57+, Firefox 52+, Edge 89+
WDR	**130 dB True WDR**
SNR	≥ 52 dB
Image Enhancement	BLC, HLC, 3D DNR
Privacy Mask	4 programmable polygon masks
On-Board Storage	microSD / SDHC / SDXC up to **512 GB**
Built-in Microphone	Yes
Reset Button	Yes
Basic Events	Motion (human & vehicle), tampering, exception
Smart Events	Scene change detection

Category	Specification
AI Functions	**Face Capture, Perimeter Protection (human/vehicle)**
Power (DC)	12 VDC ±25%, max 7.0 W
Power (PoE)	IEEE 802.3af, Class 3, max 8.5 W
Material	Full Metal (front, body, bracket)
Camera Dimensions	Ø74.4 × 179.2 mm
Package Dimensions	234 × 120 × 117 mm
Camera Weight	Approx. 525 g
Weight with Package	Approx. 750 g
Operating Temperature	-30 °C to 60 °C
Operating Humidity	≤ 95% (non-condensing)
Languages	**33 languages**
General Functions	Heartbeat, mirror, pixel counter, anti-banding
Protection Rating	**IP67**
Certifications	CE, UL, CB, KC, RCM, RoHS

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az