

DS-2CD2067G2H-LI EF

Hikvision DS-2CD2067G2H-LI EF 6 MP mini bullet IP kamera ColorVu texnologiyası ilə gecə vaxtı belə rəngli və detallı görüntü təqdim edir. Smart Hybrid Light sayəsində IR və ağ işıq avtomatik uyğunlaşır. 2.8 mm geniş bucaqlı lens, daxili mikrofon, PoE dəstəyi və IP67 qorunma səviyyəsi ilə açıq məkanlar üçün ideal təhlükəsizlik həllidir.



Specifications

Model	DS-2CD2067G2H-LI EF
Brand	Hikvision
Növ	IP
Meqapixel	5 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	40 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Metal
Yaddaş	MicroSD
Çalışma mühiti	Outdoor

KEY FEATURES

Category	Specification
Image Sensor	1/1.8" Progressive Scan CMOS
Max. Resolution	3200 × 1800 (5MP+)
Min. Illumination	Color: 0.0005 Lux @ (F1.0, AGC ON); 0 Lux with light
Shutter Time	1/3 s – 1/100,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0°–360°; Tilt: 0°–90°; Rotate: 0°–360°
Lens Type	Fixed focal lens
Focal Length Options	2.8 mm / 4 mm
Lens Mount	M16
Aperture	F1.0
Depth of Field (2.8 mm)	3.3 m – ∞
Depth of Field (4 mm)	3.8 m – ∞
FOV (2.8 mm)	H: 105.1°; V: 54.8°; D: 128.2°
FOV (4 mm)	H: 90.0°; V: 45.8°; D: 109.4°
DORI (2.8 mm)	Detect 89 m / Observe 35 m / Recognize 17 m / Identify 8 m
DORI (4 mm)	Detect 109 m / Observe 43 m / Recognize 21 m / Identify 10 m
Supplement Light Type	IR + White Light
Supplement Light Range	Up to 40 m
Smart Supplement Light	Yes
IR Wavelength	850 nm
Main Stream (50 Hz)	25 fps @ 3200×1800, 2688×1520, 1080p, 720p
Main Stream (60 Hz)	24 fps @ 3200×1800; 30 fps @ others
Sub-Stream	25/30 fps @ 720p, VGA, 640×360
Third Stream	10 fps @ 1080p, 720p, VGA, 640×360*
Video Compression	H.265/H.264/H.265+/H.264+
Video Bit Rate	32 Kbps – 16 Mbps
SVC	H.264 & H.265
Bit Rate Control	CBR / VBR
ROI	1 fixed region (main & sub-stream)
Audio Compression	G.711, G.722.1, G.726, MP2L2, PCM, MP3, AAC-LC
Audio Sampling Rate	8 / 16 / 32 / 44.1 / 48 kHz
Environment Noise Filtering	Yes
Ethernet Interface	1 × RJ45 10/100 Mbps
Network Protocols	TCP/IP, HTTP(S), FTP, DHCP, DNS, RTSP, RTP, IPv4/IPv6, SNMP, QoS, SSL/TLS, WebSocket, SFTP
API	ONVIF (Profile S/G/T), ISAPI, SDK, ISUP
Simultaneous Live View	Up to 6 channels
Max Users	Up to 32 users (Admin / Operator / User)
Security	HTTPS, 802.1X, IP filter, TLS 1.1/1.2/1.3, watermark, audit log
Network Storage	NAS (NFS, SMB/CIFS), ANR
Client Software	iVMS-4200, Hik-Connect, Hik-Central

Category	Specification
Web Browser	IE 10/11, Chrome 57+, Firefox 52+, Edge 89+
WDR	130 dB True WDR
SNR	≥ 52 dB
Image Enhancement	BLC, HLC, 3D DNR
Privacy Mask	4 programmable polygon masks
On-Board Storage	microSD / SDHC / SDXC up to 512 GB
Built-in Microphone	Yes
Reset Button	Yes
Basic Events	Motion (human & vehicle), tampering, exception
Smart Events	Scene change detection
AI Functions	Face Capture, Perimeter Protection (human/vehicle)
Power (DC)	12 VDC ±25%, max 7.0 W
Power (PoE)	IEEE 802.3af, Class 3, max 8.5 W
Material	Full Metal (front, body, bracket)
Camera Dimensions	Ø74.4 × 179.2 mm
Package Dimensions	234 × 120 × 117 mm
Camera Weight	Approx. 525 g
Weight with Package	Approx. 750 g
Operating Temperature	-30 °C to 60 °C
Operating Humidity	≤ 95% (non-condensing)
Languages	33 languages
General Functions	Heartbeat, mirror, pixel counter, anti-banding
Protection Rating	IP67
Certifications	CE, UL, CB, KC, RCM, RoHS