

DS-2CD2T23G0-I8



Model	DS-2CD2T23G0-I8
Brend	Hikvision
Növ	IP
Meqapixel	2 MP
İşıqlandırma məsafəsi	80 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	4
İşıqlandırma	İR
Qoruma	IP67
Material	Metal

Specification

<i>Camera</i>	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.01Lux @ (F1.2,AGC ON), 0.028 Lux @ (F2.0, AGCON), 0 Luxwith IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Day & Night	IR Cut Filter
Digital Noise Reduction	3D DNR
WDR	120dB
3-Axis Adjustment	Pan: 0° to 360°, tilt:0° to 100°, rotate: 0° to 360°
<i>Lens</i>	
Focal length	2.8/4/6/8 mm
Aperture	F2.0
Focus	Fixed
FOV	2.8 mm, horizontal FOV: 114°, vertical FOV: 62°, diagonal FOV: 135° 4 mm, horizontal FOV: 86°, vertical FOV: 46°, diagonal FOV: 102° 6 mm, horizontal FOV:54°, vertical FOV:30°, diagonal FOV:62° 8 mm, horizontal FOV:43°, vertical FOV:23°, diagonal FOV:50°
Lens Mount	M12
<i>IR</i>	
IR Range	-I5: Up to 50m -I8: Up to 80 m
Wavelength	850nm

<i>Compression Standard</i>	
Video Compression	Main stream: H.265/H.264 Sub-stream: H.265/H.264/MJPEG Third stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main stream supports
H.265 Type	Main Profile
H.265+	Main stream supports
Video BitRate	32 Kbps to 16 Mbps
<i>Smart Feature-set</i>	
Smart Event	Line crossing detection, intrusion detection, face detection
Basic Event	Motion detection, video tampering alarm, exception (network disconnected, IP address conflict, illegal login, HDD full, HDD error)
Linkage Method	Trigger recording: memory card, network storage, pre-record and post-record Trigger captured pictures uploading: FTP, HTTP, NAS,Email Trigger notification: HTTP, ISAPI, Email
Region of Interest	1 fixed regionfor main streamand sub-stream
<i>Image</i>	
Max. Resolution	1920 × 1080
Main Stream	50Hz: 25fps(1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps(1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream	50Hz: 25fps(640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps(640 × 480, 640 × 360, 320 × 240)

Third Stream	50Hz: 25fps (1920 × 1080, 1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1920 × 1080, 1280 × 720, 640 × 360, 352 × 240)
Image Enhancement	BLC/3D DNR/HLC
Image Setting	Rotate mode,saturation, brightness, contrast, sharpness, AGC, and white balance are adjustable by client software or web browser
Target Cropping	No
Day/Night Switch	Day/Night/Auto/Schedule/Triggered by alarm in
<i>Network</i>	
Network Storage	Support MicroSD/SDHC/SDXC card (128G), local storage and NAS (NFS,SMB/CIFS), ANR

Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour, SSL/TLS, WebSocket, WebSockets
General Function	Anti-flicker, threestreams, heartbeat, mirror, privacy masks, password reset via e-mail, pixel counter, HTTP listening
Security	Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS1.2, EAP-LEAP, EAP-MD5), watermark, IP addressfilter, basic and digest authentication for HTTP/HTTPS, WSSEand digest authentication for ONVIF, TLS1.2
API	ONVIF (PROFILE S, PROFILE G, PROFILE T), ISAPI, SDK
Simultaneous Live View	Up to 6 channels
User/Host	Up to 32 users 3 levels: Administrator, Operator and User
Client	iVMS-4200, Hik-Connect, Hik-Central
Web Browser	Plug-in required liveview: IE8+ Plug-in freelive view: Chrome57.0+, Firefox 52.0+, Safari 11+ LocalService: Chrome 41.0+,Firefox 30.0+
<i>Interface</i>	
Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
Video Output	No
On-board storage	Built-in MicroSD/SDHC/SDXC slot, up to 128 GB
SVC	H.264 and H.265 encoding
Reset Button	Yes
<i>General</i>	
Operating Conditions	-30 °C to +60 °C (-22°F to +140 °F), Humidity 95% or less(non-condensing)
Web Client Language	32 languages English, Russian, Estonian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Turkish, Korean, Traditional Chinese, Thai, Vietnamese, Japanese, Latvian, Lithuanian, Portuguese (Brazil)
Power Supply	12 VDC± 25%, Φ 5.5 mm coaxial powerplug PoE (802.3af, class 3)
Power Consumption and Current	-I5: 12 VDC, 0.6 A, max. 7.5 W PoE (802.3af, 36 V to 57 V), 0.2 A to 0.1 A, max. 9.5 W -I8: 12 VDC, 0.9 5A,max. 11.5 W PoE (802.3af, 36 V to 57 V), 0.35 A to 0.1 A, max. 12.5 W

Protection Level	IP67
Material	Metal
Dimensions	Camera: $\Phi 105 \times 299.7$ mm ($\Phi 4.1" \times 11.8"$) Package: $386 \times 156 \times 155$ mm ($15.2" \times 6.14" \times 6.1"$)
Weight	Camera: Approx. 1180 g (2.6lb.) With Package: Approx. 1700g (3.7 lb.)