

# DS-2CD2T46G2-ISU/SL

4 MP AcuSense Strobe Light and Audible Warning Fixed Bullet Network Camera; 4 MP, 60m, Audio ( Mikrofon ), DarkFighter, 120dB WDR, IP67



## Specifications

Model	DS-2CD2T46G2-ISU/SL
Brand	Hikvision
Növ	IP
Meqapixel	4 MP
???qland?rma m?saf?si	60 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
???qland?rma	IR
Qoruma	IP67
Material	Metal
Yadda?	MicroSD
?? mühiti	Outdoor

## KEY FEATURES

<b>Camera</b>	
<b>Image Sensor</b>	1/3" Progressive Scan CMOS
<b>Min. Illumination</b>	Color: 0.003 Lux@ (F1.4, AGC ON), B/W: 0 Lux with IR
<b>Shutter Speed</b>	1/3 s to 1/100,000 s
<b>Slow Shutter</b>	Yes
<b>P/N</b>	P/N
<b>Wide Dynamic Range</b>	120 dB
<b>Day &amp; Night</b>	IR cut filter
<b>Angle Adjustment</b>	Pan: 0° to 360°, tilt:0° to 90°, rotate: 0° to 360°
<b>Lens</b>	
<b>Lens Type</b>	Fixed focallens, 2.8, 4, and 6 mm optional
<b>Iris Type</b>	Fixed
<b>Focal Length&amp; FOV</b>	2.8 mm, horizontal FOV: 103°, vertical FOV: 55°, diagonal FOV: 123° 4 mm, horizontal FOV: 83°, vertical FOV: 45°, diagonal FOV: 98° 6 mm, horizontal FOV:53°, vertical FOV: 29°, diagonal FOV: 62°
<b>Aperture</b>	F1.4
<b>Lens Mount</b>	M12
<b>DORI</b>	2.8 mm: D: 60.0m, O: 23.8m, R: 12.0 m, I: 6.0 m
<b>DORI</b>	4 mm: D: 80.0m, O: 31.7 m, R: 16.0m, I: 8.0 m
<b>DORI</b>	6 mm: D: 120.0m, O: 47.6 m, R: 24.0 m, I:12.0 m
<b>Illuminator</b>	
<b>Supplement LightType</b>	IR
<b>IR Range</b>	Up to 60 m
<b>IR Wavelength</b>	850 nm
<b>Smart Supplement Light</b>	Yes
<b>Visual Alarm</b>	Yes
<b>Video</b>	
<b>Max. Resolution</b>	2688 × 1520
<b>Main Stream</b>	50 Hz: 25 fps(2688 × 1520,1920 × 1080,1280 × 720) 60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 ×720)
<b>Sub-Stream</b>	50 Hz: 25 fps (1280 × 720, 640 × 480,640 × 360) 60 Hz: 30 fps (1280 × 720, 640 ×480, 640 × 360)

	50 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)
Third Stream	60 Hz: 10 fps (1920 × 1080, 1280 × 720, 640 × 480, 640 × 360)
	*Third stream is supported under certain settings.
	Main stream: H.265/H.264/H.265+/H.264+
	Sub-stream: H.265/H.264/MJPEG
Video Compression	Third stream: H.265/H.264
	*Third stream is supported under certain settings.
Video Bit Rate	32 Kbps to 8 Mbps
H.264 Type	Baseline Profile/Main Profile/High Profile
H.265 Type	Main Profile
H.264+	Main stream supports
H.265+	Main stream supports
Bit Rate Control	CBR/VBR
Scalable Video Coding(SVC)	H.264 and H.265 encoding
Region of Interest (ROI)	1 fixed region for main stream and sub-stream
Audio	
Environment Noise Filtering	Yes
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz
Audio Compression	G.711 ulaw/G.711 alaw/G.722.1/G.726/ MP2L2/PCM/MP3/AAC-LC
Audio Bit Rate	64 Kbps (G.711 ulaw/G.711 alaw)/16 Kbps (G.722.1)/ 16 Kbps (G.726)/32 to 192 Kbps (MP2L2)/8 to 320 Kbps (MP3)/16 to 64 Kbps (AAC-LC)
Network	
Simultaneous Live View	Up to 6 channels
API	Open Network Video Interface (PROFILE S, PROFILE G, PROFILE T), ISAPI, SDK
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, ARP, WebSocket, WebSockets
User/Host	Up to 32 users. 3 user levels: administrator, operator and user
Security	Password protection, complicated password © 2026 Hikvision. All rights reserved.   Eurotechnology HTTPS encryption, IP address filter,