

# DS-2CE10HFT-F28

Model	DS-2CE10HFT-F28
Brend	Hikvision
Növ	Analoq
Meqapixel	5 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8
Qoruma	IP67
Material	Metal



## Specification

Camera	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Resolution	2560 (H) × 1944(V)
Frame Rate	TVI: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080p@30fps, 1080p@25fps CVI: 4MP@30fps, 4MP@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps CVBS: PAL/NTSC
Min. illumination	0.0005 Lux @ (F1.0,AGC ON), 0 Lux with White Light
Shutter Time	PAL: 1/25s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm fixed lens
Horizontal Field of View	2.8 mm, horizontal FOV:99.7°, vertical FOV:72°, diagonal FOV:139.8°
Lens Mount	M16
Day & Night	Color
WDR (Wide DynamicRange)	≥130 dB
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 90°, Rotation: 0 to 360°
Menu	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT
AGC	Yes

<b>Day/Night Mode</b>	<b>Color</b>
<b>White Balance</b>	<b>Auto/Manual</b>
<b>AE (Auto Exposure) Mode</b>	<b>WDR/BLC/HLC/Global/HLS/Anti-banding</b>
<b>Privacy Mask</b>	<b>4 programmable privacy masks</b>
<b>Motion Detection</b>	<b>4 programmable motion areas</b>
<b>Noise Reduction</b>	<b>3D DNR</b>
<b>Language</b>	<b>English</b>
<b>Function</b>	<b>Brightness, Sharpness, Mirror, Smart Light</b>
<b>Interface</b>	
<b>Video Output</b>	<b>Switchable TVI/AHD/CVI/CVBS</b>
<b>General</b>	
<b>Operating Conditions</b>	<b>-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less(non-condensing)</b>
<b>Power Supply</b>	<b>12 VDC ± 25%</b>
<b>Power Consumption</b>	<b>Max. 3.5W</b>
<b>Protection Level</b>	<b>IP67</b>
<b>Material</b>	<b>Metal</b>
<b>White Light Range</b>	<b>Up to 20 m</b>