

# DS-2CE10KF0T-PFS

NVR for IP Cameras



## Specifications

Model	DS-2CE10KF0T-PFS
Brand	Hikvision
?? mühiti	Outdoor
Növ	Analoq
Meqapixel	4 MP
???qland?rma	LED
???qland?rma m?saf?si	20 m
Mikrofon	Mic
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Plastik

## KEY FEATURES

<b>Camera</b>	
<b>Image Sensor</b>	3K CMOS
<b>Signal System</b>	PAL/NTSC
<b>Resolution</b>	2960 (H) × 1665 (V)
	TVI: 3K@20fps, 4 MP@25fps/30fps, 1080p@25fps/30fps AHD: 5MP@20fps, 4 MP@25fps/30fps
	CVI: 4 MP@25fps/30fps
<b>Frame Rate</b>	CVBS: PAL/NTSC
<b>Min. Illumination</b>	0.001 Lux @ (F1.0, AGC ON), 0 Lux with whitelight
<b>Shutter Time</b>	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
<b>Lens</b>	2.8 mm and 3.6 mm fixed focal lens
<b>Field of View</b>	2.8 mm, horizontal FOV: 102°, vertical FOV: 56°, diagonal FOV: 122°
	3.6 mm, horizontal FOV:80°, vertical FOV: 45°, diagonal FOV: 96°
<b>Lens Mount</b>	M12
<b>Light Alarm</b>	Solid Light Alarm(White Light)
<b>Day &amp; Night</b>	24/7 Color Imaging
<b>WDR (Wide Dynamic Range)</b>	Digital WDR
<b>Angle Adjustment</b>	Pan: 0° to 360°, Tilt:0° to 90°, Rotation: 0° to 360°
<b>Image</b>	
<b>White Light</b>	Auto/Off
<b>Image Mode</b>	STD/HIGH-SAT/HIGHLIGHT
<b>AGC</b>	Yes
<b>Day/Night Mode</b>	Color
<b>White Balance</b>	Auto/Outdoor/Global/Manual
<b>AE (Auto Exposure) Mode</b>	DWDR,BLC,HLC,Global,HLS
<b>Noise Reduction</b>	2D DNR
<b>Language</b>	English
<b>Function</b>	Brightness,Contrast,Mirror,Defective Pixel Correction,Sharpness,Anti-Banding,Smart Light
<b>Interface</b>	
<b>Video Output</b>	Switchable TVI/AHD/CVI/CVBS
<b>Audio In</b>	Built-in mic
<b>General</b>	
<b>Operating Conditions</b>	-40°C to 60°C (-40°Fto 140°F), Humidity: 90% or less(non-condensing)
<b>Power Supply</b>	12 VDC ± 25%,
<b>Consumption</b>	Max. 2.5 W
<b>Protection Level</b>	IP67
<b>Material</b>	Plastic
<b>White LightRange</b>	Up to 20 m

---

<b>Communication</b>	<b>HIKVISION-C</b>
<b>Dimension</b>	<b>161.1 mm × 70 mm × 70 mm (6.34" × 2.76" × 2.76")</b>
<b>Weight</b>	<b>Approx. 238 g (0.52lb.)</b>