

DS-2CE11H0T-PIRL

Hikvision DS-2CE11H0T-PIRL 5 mp meqapiksel TVI PIR video kamera; Piksel 2560×1944; IR işıqlandırma - 20 m; F2.8 mm; Bucaq-85.5°;

Model	DS-2CE11H0T-PIRL
Brend	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	5 MP
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	2.8mm
İşıqlandırma	İR
Material	Metal
İş mühiti	Outdoor



Specification

<i>Camera</i>	
Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Frame Rate	TVI: 5 MP@20fps, 4 MP@25fps, 4 MP@30fps, 1080P@25fps, 1080P@30fps
Resolution	2560 (H) × 1944 (V)
Min. Illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/20 s to 1/50,000 s NTSC: 1/20 s to 1/50,000 s
Lens	2.8 mm, 3.6 mm fixedfocal lens
Field of View	2.8 mm, horizontal FOV: 85.5°, vertical FOV:63.8°, diagonal FOV: 110.7° 3.6 mm, horizontal FOV: 80.1°, vertical FOV: 63.8°,diagonal FOV: 105.9°
Lens Mount	M12
Strobe Light Alarm	Yes
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0° to 360°, Tilt:0° to 180°, Rotate: 0° to 360°
<i>Menu</i>	
White Light	AUTO/OFF
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	Auto/Manual

AE (Auto Exposure) Mode	DWDR/BLC/HLC/Global
Noise Reduction	2D DNR
Language	English
Function	Brightness, Sharpness, Mirror, Smart IR
<i>Interface</i>	
Video Output	1 HD analog output
<i>General</i>	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensing)
Power Supply	12 VDC ±25%
Power Consumption	Max. 4 W
Ingress Protection	IP67
Material	Metal
IR Range	Up to 20 m
White LightRange	Up to 20 m
PIR Range	Angle: 110°, Range: 11 m
Communication	HIKVISION-C
Dimensions	68 mm × 70 mm × 179.8 mm (2.68" × 2.76" × 7.08")
Weight	Approx. 358 g (0.79 lb.)