

DS-2CE12DF3T-F

Hikvision DS-2CE12DF3T-F 2 mp meqapiksel TVI ColorVu (rəngli) video kamera; Piksel 1920×1080; LED işıqlandırma - 40 m; F3.6 mm; Bucaq-77°;

Model	DS-2CE12DF3T-F
Brend	Hikvision
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	40 m
Obyektiv	Sabit
Fokus	3.6
Qoruma	IP67
Material	Metal



Specification

Camera	
Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080(V)
Frame Rate	TVI: 1080p@25fps/30fps CVI: 1080p@25fps/30fps AHD: 1080p@25fps/30fps CVBS: PAL/NTSC
Min. Illumination	0.0005 Lux @ (F1.0, AGCON), 0 Lux with whitelight ON
Shutter Time	PAL: 1/25s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm, 3.6 mm, 6 mm FixedLens
Field of View	2.8 mm, horizontal FOV: 98°, vertical FOV: 52°, diagonal FOV: 116° 3.6 mm, horizontal FOV: 77°, vertical FOV: 42°, diagonal FOV: 91° 6 mm, horizontal FOV: 51°, vertical FOV: 28°, diagonal FOV: 59°
Lens Mount	M12
Light Alarm	Solid LightAlarm (White Light)
Day & Night	Color
WDR (Wide Dynamic Range)	≥130 dB
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°

Menu	
White Light	Auto/Off
Image Mode	STD/HIGH-SAT/HIGHLIGHT
AGC	Yes
Day/Night Mode	Color
White Balance	Auto/Manual
AE (Auto Exposure) Mode	WDR, BLC,HLC, Global, HLS
Privacy Mask	4 programmable privacymasks
Motion Detection	4 programmable motionareas
Noise Reduction	3D DNR/2D DNR
Language	English
Function	Brightness, Contrast, Mirror,Defective Pixel Correction, Sharpness, Anti-Banding, Smart Light
Lighting Mode	White Light
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40°C to 60°C (-40°Fto 140°F), Humidity: 90% or less(non-condensing)
Power Supply	12 VDC ± 25%, <i>*You are recommended to use onepower adapter to supply the power for one camera.</i>
Consumption	Max. 4.2 W
Protection Level	IP67
Material	Metal
White Light Range	Up to 40 m
Communication	HIKVISION-C
Dimension	194.2 mm × 78 mm × 74.5 mm (7.65" × 3.07" × 2.93")
Weight	Approx. 514.5 g (1.13 lb.)