

DS-2CE12KF3T-L

DS-2CE12KF3T-L 3.6mm 5mp IR-LED 40m 3K ColorVu Dual-light Fixed Bullet KAMERA
HIKVISION

| | |
|-----------------------|----------------|
| Model | DS-2CE12KF3T-L |
| Brend | Hikvision |
| Qoruma | IP67 |
| Növ | Analoq |
| Meqapixel | 5 MP |
| İşıqlandırma | LED |
| İşıqlandırma məsafəsi | 40 m |
| Obyektiv | Sabit |
| Fokus | 3.6mm |
| Material | Metal |
| İş mühiti | Outdoor |



Specification

| | |
|-------------------------|---|
| Camera | |
| Image Sensor | 3K CMOS |
| Signal System | PAL/NTSC |
| Max. Resolution | 2960 (H) × 1665(V) |
| Slow Shutter | Max. 16 times |
| Min. Illumination | 0.0005 Lux @ (F1.0,AGC ON), 0 Lux withwhite light |
| Shutter Time | PAL: 1/25s to 1/50,000 s;NTSC: 1/30s to 1/50,000 s |
| Angle Adjustment | Pan: 0° to 360°,Tilt: 0° to 180°, Rotate: 0° to 360° |
| Lens | |
| Lens Type | 2.8 mm and 3.6 mm fixedfocal lens |
| Focal Length FOV | 2.8 mm, horizontal FOV:110°, vertical FOV: 59°, diagonal FOV: 139° 3.6 mm, horizontal FOV:90°, vertical FOV: 49°, diagonal FOV: 105° |
| Lens Mount | M12 |
| Illuminator | |
| Supplement LightRange | IR: Up to 40 m,White Light:Up to 40 m |
| Smart Supplement Light | Yes |
| Image | |
| Frame Rate | 3K @20 fps, 4 MP @25 fps/30 fps, 1080p @25 fps/30 fps |
| Privacy Mask | 4 programmable privacy masks/8programmable privacymasks |
| Wide Dynamic Range(WDR) | ≥130 dB |
| Image Parameters Switch | STD/HIGH-SAT/HIGHLIGHT |
| AGC | Yes |
| Day/Night Mode | Auto/Color/BW (Blackand White) |
| White Balance | Auto/Outdoor/Global/Manual |
| Image Enhancement | WDR,BLC,HLC,Global,HLS |

| | |
|---------------------|---|
| Noise Reduction | 3D DNR/2D DNR |
| Image Settings | Brightness, Contrast, Mirror, Smart Light, Anti-Banding |
| Interface | |
| Video Output | 1 HD analog output |
| Event | |
| Motion Detection | 4 programmable motion areas |
| General | |
| Power | 12 VDC \pm 25%, 0.65 A, max. 7.8 W, *You are recommended to use one power adapter to supply the power for one camera. |
| Language | English |
| Operating Condition | -40 °C to 60 °C (-40°F to 140 °F). Humidity: 90% or less (non-condensing) |
| Material | Metal |
| Communication | HIKVISION-C |
| Dimension | 194.2 mm \times 78 mm \times 74.5 mm (7.65" \times 3.07" \times 2.93") |
| Weight | Approx. 535g (1.18 lb.) |
| Approval | |
| Protection | IP67 |