HIKVISION

DS-2CE12KF3T-L

Kod: 00-00005969 · Kamera



Hikvision DS-2CE12KF3T-L (2.8mm) – 3K (2960 × 1665) təsvir ölçülü və ColorVu texnologiyalı Smart Dual-Light analoq bullet kameradır. F1.0 diafraqması sayəsində gecə-gündüz rəngli təsvir verir. 40 metrə qədər İQ və ağ işıqlandırması, 130 dB True WDR və IP67 dözümlü metal korpusa malikdir.

Texniki göstəricilər

Analoq Növ	**5 MP** Meqapixel
LED İşıqlandırma	**40 m** İşıqlandırma məsafəsi
Sabit Obyektiv	**2.8mm** Fokus
IP67 Qoruma	**Metal** Material
Outdoor İş mühiti	

Ətraflı məlumat

Parameter	Specification
Brand	Hikvision
Model	DS-2CE12KF3T-L (2.8mm)
Camera Type	Fixed Bullet Camera
Image Sensor	3K CMOS
Max. Resolution	3K / 5 MP (2960 × 1665)
Min. Illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light
Lens Focal Length	2.8 mm fixed focal lens
Field of View (FoV)	Horizontal FOV: 105°, Vertical FOV: 59°, Diagonal FOV: 139°
Aperture	F1.0 (24/7 Color Imaging)
Supplement Light Type	Smart Dual-Light (IR & White Light)
Illumination Distance	IR: Up to 40 m / White Light: Up to 40 m
Wide Dynamic Range (WDR)	≥130 dB True WDR
Noise Reduction	3D DNR / 2D DNR
Frame Rate	3K @ 20 fps, 4 MP @ 25/30 fps, 1080p @ 25/30 fps
Video Output	1 HD Analog Output (TVI / AHD / CVI / CVBS switchable)
Ingress Protection	IP67 (Water and Dust Resistant)
Material	Metal Body
Power Supply	12 VDC ± 25%, Max. 7.8 W
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less
Dimensions	194.2 mm × 78 mm × 74.5 mm
Weight	Approx. 535 g

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az