

DS-2CE16D0T-EXLPF

DS-2CE16D0T-EXLPF 2.8mm 2mp Smart IR 20m LED 20m HD MINI BULLET KAMERA HIKVISION



Specifications

Model	DS-2CE16D0T-EXLPF
Brand	Hikvision
Növ	Analoq
Meqapixel	2 MP
???qland?rma	LED
???qland?rma m?saf?si	20 m
Obyektiv	Sabit
Fokus	2.8mm
Qoruma	IP67
Material	Plastik
?? mühiti	Outdoor

KEY FEATURES

Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080(V)
Min. Illumination	0.02 Lux@ (F2.2, AGCON), 0 Lux with IR
Shutter Time	PAL: 1/25s to 1/50,000 s; NTSC:1/30 s to 1/50,000 s
Day &Night	ICR
Angle Adjustment	Pan: 0 to 360°,Tilt: 0 to 90°, Rotate: 0 to 360°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm,3.6 mm fixedfocal lens
Focal Length& FOV	2.8 mm,horizontal FOV: 97°, vertical FOV: 54°, diagonal FOV: 113°
	3.6 mm, horizontal FOV: 77°, vertical FOV: 43°, diagonal FOV: 90°
Lens Mount	M12
Illuminator	
Supplement LightType	Smart,IR,White Light
Supplement LightRange	IR : Up to 20 m
	White Light: Up to 20 m
Image	
Image Parameters Switch	STD/HIGH-SAT/HIGHLIGHT
Image Settings	Brightness, Sharpness, Smart IR
	TVI: 1080p @ 30 fps, 1080p @ 25 fps AHD: 1080p @ 30 fps, 1080p@ 25 fps CVI: 1080p @ 30 fps, 1080p @ 25 fps
Frame Rate	CVBS: PAL/NTSC
Day/Night Mode	Auto/Color
Wide Dynamic Range (WDR) Digital WDR	
Image Enhancement	DWDR/BLC/HLC/Global
White Balance	Auto/Manual
AGC	Yes
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Material	Plastic
Dimension	Ø70 mm × 138.8mm (Ø2.76" x 5.46")
Weight	Max. 150 g (0.33lb.)
Operating Condition	-40 °C to 60 °C (-40°F to 140 °F). Humidity: 90% or less(non-condensation)
Communication	HIKVISION-C
Language	English

12 VDC ± 25%,Max. 3.2 W

Power Supply	*You are recommended to use onepower adapter to supply the power for one camera.
Approval	
Protection	IP67