

DS-2CE16D0T-ITF

Hikvision Analoq Kamera 2MP- DS-2CE16D0T-ITF 2,8/MM



Specifications

Model	DS-2CE16D0T-ITF
Brand	Hikvision
Qoruma	IP67
Növ	Analoq
Meqapixel	2 MP
??qland?rma m?saf?si	30 m
Obyektiv	Sabit
Fokus	2.8mm
??qland?rma	IR
Material	Metal
?? mühiti	Outdoor

KEY FEATURES

Camera

Image Sensor	2 MP CMOS
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V) TVI: 1080P@30fps, 1080P@25fps CVI: 1080P@30fps, 1080P@25fps AHD: 1080P@30fps, 1080P@25fps CVBS: PAL/NTSC
Frame Rate	
Min. illumination	0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50,000 s
Lens	2.8 mm, 3.6 mm, 6 mm fixedlens 2.8 mm, horizontal FOV: 99.5°, vertical FOV: 53.7°, diagonal FOV: 116.5°
Field of View	3.6 mm, horizontal FOV: 76.4°, vertical FOV: 41.9°, diagonal FOV: 89.6° 6 mm, horizontal FOV: 49.2°, vertical FOV: 28.3°, diagonal FOV: 56.1°
Lens Mount	M12
Day & Night	ICR
WDR (Wide Dynamic Range)	Digital WDR
Angle Adjustment	Pan: 0 to 360°, Tilt: 0 to 90°, Rotation: 0 to 360°
Menu	
Image Mode	STD/HIGH-SAT
AGC	Yes
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	Auto/Manual
AE (Auto Exposure) Mode	Global/BLC/HLC/DWDR
Noise Reduction	2D DNR
Language	English
Function	Brightness, Sharpness, SmartIR
Interface	
Video Output	Switchable TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Power Supply	12 VDC ± 25%
Power Consumption	Max. 3 W
Protection Level	IP67
Material	Metal
IR Range	Up to 30 m
Communication	HIKVISION-C
General	
Dimensions	57.9 mm × 60.9 mm × 138.8 mm (2.28" × 2.39" × 5.47")
Weight	Approx. 257 g (0.57 lb.)